





	ACCESS CONTROL PANEL ACCO-NT2 SATEL	ANGULAR COUPLER LK-90X40/W STASINSKI	CLEANING PASTE PEVALIN- PROFESSIONAL/250 TUBE 250 ml TESA	SWITCHING ADAPTER FIBRE-IRS/POWERSUPPLY
				
	319.87 GBP 319.87 GBP	6.52 GBP 6.52 GBP	6.94 GBP 6.94 GBP	18.64 GBP 18.64 GBP
Length	...	126 mm
Adapter type	Switching
Width	...	126 mm
Package	Tube 250 ml	...
Depth	...	41 mm
Power voltage	100 ... 240 V AC
Frequency range	50/60 Hz
Inputs	• 8 pcs - Mainboard inputs • max. 264
Color	...	White
Output voltage	20 V DC
Maximal load	1.2 A
Power	24 W
Application	FibreIRS optical kit
Outputs	• 8 pcs - Mainboard inputs • max. 264
Output	2.1/5.5 mm plug
Communication	• 2 x RS-485 • Expander bus - up to 32 expander modules
Events memory	• Events saving to the micro SD card (included) • Recording up to 1 000 000 events from the control panel, • Max. 100 000 events read from each access control module
Users + admins	• 8000 + 1 • Max. 65 000 users in the whole ACCO NET system
Output load	• OC : 50 mA / 12 V DC • +EX : 0.5 A / 12 V DC • AUX : 0.5 A / 12 V DC

Main features	<ul style="list-style-type: none"> • Support for up to 255 access control modules • Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition) • Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway) • Ability to block/unblock partition at a specified time, or as per access schedule, • Ability to assign 4 identifiers and a keyfob to a single user, • Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user, • Up to 256 access calendars, weekly schedules, daily schedules, time frames • Ability to control the control panel outputs by using keyfobs • Implementation of logic functions on inputs and outputs • Support for turnstiles • Electrical protection of all inputs and outputs as well as communication buses
Power supply	12 V DC / 140 mA (max)
Battery backup support	—
Operation temp	-10 °C ... 55 °C
Permissible relative humidity	93 % (non-condensing)
Weight	0.096 kg	0.71 kg	...	0.16 kg
Dimensions	151 x 69 x 17 mm
Manufacturer / Brand	SATEL	STASINSKI	TESA	...
Guarantee	2 years	2 years	2 years	2 years