




	FLUSH BOX PK-60/K-G/SG/EPN Elektro-Plast	ELECTRICAL INSTALLATION BOX INTO THERMAL INSULATION KUZ-VOI-KB KOPOS	EXTENDER HDMI-EX-120-4K-V4
			
	0.90 EUR 0.90 EUR	41.82 EUR 41.82 EUR	178.54 EUR 178.54 EUR
Supported HDMI standard	1.4
HDCP	1.4
Number of sections	1	1, 2	...
Protocols	HDbiT
"Index of Protection"	—	IP30 / IP44	...
Voltage insulation	...	~ 400 V	...
Montage hole diameter	Ø 68 mm
Supported HDMI resolutions	<ul style="list-style-type: none"> • 480i @ 60Hz, • 480p @ 60Hz, • 576i @ 50Hz, • 576p @ 50Hz, • 720p @ 50/60Hz, • 1080i @ 50/60Hz, • 1080p @ 50/60Hz, • 4K UHD @ 24/25/30Hz
Material	halogen free and inflammable	Non-halogen plastic	...
Color	Yellow	Light gray	...
Maximal transmission range	<ul style="list-style-type: none"> • 80 m UTP cat. 5 • 100 m UTP cat. 5e • 120 m UTP cat. 6
Weight	0.024 kg	0.735 kg	...
Thickness of the insulating layer	...	120 ... 330 mm	...
Mounting holes distance	...	60 mm, 71 mm	...
Main features	<ul style="list-style-type: none"> • Flush-mounted, for hollow walls • 850 °C flammability index • 2 special screws with holders to fastening to the wall - included 	<ul style="list-style-type: none"> • for insulating systems • temperature range : -25 °C ... 60 °C • flammability index : 850 °C • adjustable depth of the box • Guides for attaching the TS35 rail • Expansion plugs, Mounting screws, opening lid, rubber gasket - included 	<ul style="list-style-type: none"> • IR carrier frequency : 20 kHz ... 60 kHz • Protections : lightning, Overvoltage, ESD
Power supply	5 V DC / 2 A (2 pcs of power supply adapters included)
Current consumption	<ul style="list-style-type: none"> • 4 W Receiver • 6 W Transmitter

Manufacturer / Brand	Elektro-Plast	KOPOS	...
Operation temp	0 °C ... 60 °C
Transmitter and receiver weight	0.33 kg
Dimensions	Ø 60 x 47 mm - Internal dimensions Ø 67 x 48 mm - External dimensions	196 x 156 x 86 ... 146 mm (box) 210 x 170 x 12 mm (cover) 120 x 120 x 200 mm (carrier)	113 x 95 x 24 mm
Guarantee	2 years	2 years	2 years