



	<a href="#">PARKING SENSOR LED LIGHTING CONTROLLER PARKING-SENSOR/BLEBOX 7... 24 V DC</a>	<a href="#">CONNECTION BOX PUH-3PK</a>
		
	325.15 NOK 325.15 NOK	64.36 NOK 64.36 NOK
Number of intakes	...	2
Voltage insulation	...	450 V
Application	<ul style="list-style-type: none"> <li>• It shows the distance between the moving object and the sensor by using LED lighting</li> <li>• Works with LED lighting - (RGB) 7-24V LED strips</li> </ul>	...
Cable diameter	...	Ø 4 ... Ø 9 mm
Rated voltage	7 ... 24 V DC	...
Maximal total load	56 ... 192 W	...
Total maximal current	8 A	...
Internal dimensions	...	70 x 44 x 29 mm - From the 70 mm dimension, the thickness of the gland nuts should be subtracted, which enter the box to a depth of 5 mm each
Number of inputs	0	...
Number of outputs	4	...
Connector type	screw terminals	...
Wireless	—	...
Mobile phones support	—	...

Main features	<ul style="list-style-type: none"> <li>• Ultrasonic sensor,</li> <li>• Outputs : "Open Collector" (OC) type 250 mA,</li> <li>• Distance range of the virtual wall from the sensor : 2 ... 250 cm,</li> <li>• Operation modes (distances to virtual wall) : <ul style="list-style-type: none"> <li>- Green : 140 cm (safe distance)</li> <li>- Blue : 48 ± 4 cm (obstacle close)</li> <li>- Red : 17 ± 3 cm (stop the vehicle)</li> <li>- Red (blinking) : 4 ± 2 cm (stop the vehicle immediately)</li> </ul> </li> <li>• Additional output for space occupancy signaling,</li> <li>• Small dimensions</li> </ul>	...
Housing	Self-extinguishing	...
"Index of Protection"	IP20	IP66
Color	Black	...
Operation temp	-20 °C ... 50 °C	...
Weight	0.06 kg	...
Dimensions	51 x 58 x 25 mm	125 x 60 x 36 mm
Manufacturer / Brand	BleBox	...
Guarantee	2 years	2 years