



	IP CAMERA TC-C34QN SPEC:15W/E/Y/2.8MM/V4.2 - 4 Mpx 2.8 mm TIANDY	SPEAKER CABLE HI- FI/2X0.35
		
	88.09 GBP 88.09 GBP	0.18 GBP 0.18 GBP
Standard	IP	...
Sensor	1/2.9 " Progressive Scan CMOS	...
In section	...	100 m . Price for 1m when buying a whole roll
Inner conductor	...	2 x Ø 0.35 mm Cu-OFC Stranded wire
Outer coating	...	PVC
Coating color	...	Colorless
Resolution	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	...
Lens	2.8 mm	...
View angle	100 °	...
Range of IR illumination	50 m	...
White light LED illuminator range	15 m	...
Memory card slot	—	...
Image compression method	S+265 / H.265 / H.264	...
Alarm inputs / outputs	—	...
Audio	• Microphone built-in • Audio transmission via network	...
Main stream frame rate	25 fps @ 4 Mpx	...
Network interface	10/100 Base-TX (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	2	...
ONVIF	✓	...
Mobile phones support	Port no.: 3000 or access by a cloud (P2P) • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus	...

Access from PC	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Default IP address	DHCP or 192.168.1.2	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Web browser access ports	80, 433, 3000, 3001, 3002, 23002	...
Mobile client access ports	3000, 3001	...
PC client access ports	3000, 3001	...
Port ONVIF	80	...
Intelligent image analysis	<ul style="list-style-type: none"> • crossing the line (tripwire) • intrusion 	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Possibility to change the resolution, quality and bit rate 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 590 mA 	...
Power consumption	≤ 7 W	...
Housing	Compact - Metal + Plastic	...
Color	White	...
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.23 kg	...
Dimensions	164 x 72 x 72 mm	...

Supported languages	Polish, English, Chinese, Spanish, Korean, Italian, Turkish, Russian, Thai, French, Dutch, Hebrew, Arabic, Vietnamese, German, Ukrainian, Portuguese, Albanian	...
Manufacturer / Brand	TIANDY	...
Guarantee	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00