



	<a href="#">WIRELESS PIR DETECTOR MPD-310 SATEL</a>	<a href="#">AC POWER SUPPLY ADAPTER PSAC-08246 METAL ENCLOSURE TRANSFORMING</a>
		
	129.00 PLN 129.00 PLN	428.00 PLN 428.00 PLN
Adapter type	...	Transforming
Support	Satel MICRA	...
Output voltage	...	24 / 27 V AC
Frequency range	433.05 ... 434.79 MHz	...
Output voltage adjustment	...	✓ (step adjustment)
Max. output current (total)	...	6 A
Max. output current for single output	...	0.75 A
Outputs protection	...	1 A Polymer / Fuse
LED indication	...	✓
AW output (fault) - OC type 50mA, LED indication of at least one output fault	...	✓
Radio communication range (at open area)	<ul style="list-style-type: none"> <li>• ≤ 600 m @ PERFECTA</li> <li>• ≤ 500 m @ VERSA-MCU / MTX-300 / MICRA</li> <li>• ≤ 250 m @ MRU-300</li> </ul>	...
Protection	...	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overheat</li> <li>• Overvoltage</li> <li>• Tamper</li> </ul>
Input voltage	...	230 V @ 50Hz
Power	...	150 VA
Number of outputs	...	8
Connector type	...	Cable terminals
Housing type	...	Metal, wall-mounted
Key closed	...	—
Detection angle / Detection range	<ul style="list-style-type: none"> <li>• 92 ° / 18 m x 16.5 m - high sensitivity</li> <li>• 82 ° / 14 m x 11.5 m - normal sensitivity</li> </ul>	...
Pet immunity	—	...
Power supply	CR123A 3 V (included)	...
Battery lifetime	~ 3 years	...
Recommended installation height	2.4 m	...
Protection class (Grade)	Grade 2	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Environment class	II	...
Main features	<ul style="list-style-type: none"> <li>• digital detection algorithm with temperature compensation for high immunity to false alarms and repeatability of parameters</li> <li>• ability to change sensitivity to match optimum detector parameters to the protected space</li> <li>• Option to enable / disable approach zone control</li> <li>• LED diodes indicating the device operation status</li> <li>• Transmission encryption</li> <li>• Interchangeable Fresnel lenses</li> <li>• Tamper detection - opening the enclosure, removing from mounting surface</li> <li>• energy management system to enable many years of operation without having to replace the CR123A Lithium battery</li> </ul>	...
Operation temp	-10 °C ... 55 °C	...
Dimensions	62 x 137 x 42 mm	246 x 215 x 64 mm
Weight	0.12 kg	3.0 kg
Manufacturer / Brand	SATEL	PULSAR
Guarantee	2 years	2 years