



	ANCHOR FOR CONCRETE KOT-M12X450	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1801T-Z- A-27135-S2 - 8.3 Mpx 2.7 ... 13.5 mm - MOTOZOOM DAHUA
		
	3.46 EUR 3.46 EUR	203.35 EUR 203.35 EUR
Application	For MK-1.5/POD-HD base	...
Material	Steel galvanized - Hot-dip galvanized	...
Threaded Rod	M12	...
Standard	...	AHD, HD-CVI, HD-TVI, CVBS
Sensor	...	Progressive Scan CMOS
Matrix size	...	8.3 Mpx
Resolution	...	<ul style="list-style-type: none"> • AHD / HD-CVI / HD-TVI : 3840 x 2160 - 8.3 Mpx, 4K UHD • HD-CVI : 2880 x 1620 - 5 Mpx 2560 x 1440 - 3.7 Mpx • CVBS : 960 x 576 - 960H
Lens	...	2.7 ... 13.5 mm - Motozoom, AutoFocus
View angle	...	<ul style="list-style-type: none"> • 114 ° ... 32 ° (manufacturer data) • 110 ° ... 31 ° (our tests result)
Range of IR illumination	...	60 m
IR illuminator power adjustment	...	Automatic
Video output	...	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω
Audio	...	Microphone built-in - HD-CVI only

Main features	...	<ul style="list-style-type: none"> • Motozoom lens, AutoFocus - The control possible only from Dahua recorders in HD-CVI mode • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • D-ZOOM - Digital Zoom • Mirror - Mirror image • Privacy zones - max. 8 • Sharpness - sharper image outlines
OSD menu	...	OSD menu available via DAHUA recorder
Power supply	...	12 V DC / 660 mA
Power consumption	...	≤ 7.9 W
Housing	...	Dome, Metal
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.39 kg	0.59 kg
Dimensions	450 x 70 x 10.5 mm	Ø 122 x 105 mm
Manufacturer / Brand	...	DAHUA
Guarantee	2 years	3 years