





	EXPANSION PLUG KW-6/3.5X50 KLIMAS	EXPANSION PLUG KS-10/6X100 KLIMAS	EXPANSION PLUG KW-8/4X45 KLIMAS	ROUTER ARCHER-AX10 Wi-Fi 6 2.4 GHz, 5 GHz 1201 Mbps + 300 Mbps TP-LINK
				
	0.29 PLN 0.29 PLN	1.06 PLN 1.06 PLN	0.29 PLN 0.29 PLN	247.54 PLN 247.54 PLN
Frequency range	2.4 GHz, 5 GHz
Antenna type	4 x Omnidirectional antenna
Material	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized 	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized 	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized 	...
Drilling diameter	6 mm	10 mm	8 mm	...
Expansion plug length	30 mm	60 mm	40 mm	...
Standards	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11ax/ac/n/a @ 5 GHz
Baud rates	1201 Mbps + 300 Mbps
Screw dimensions	Ø 3.5 x 50 mm, PZ-2	Ø 6 x 100 mm, SW-10	Ø 4 x 45 mm, PZ-2	...
Application	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick 	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick 	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick 	...
LAN ports	1 x 10/100/1000 Mbps - Uplink 4 x 10/100/1000 Mbps - LAN
LED indicators	Power, 2.4 GHz WLAN, 5 GHz WLAN, INTERNET, LAN, USB

Receiver sensitivity	2.4 GHz : <ul style="list-style-type: none"> • 11g 6M : -91 dBm • 11g 54M : -74 dBm • 11n HT20 MCS0 : -90 dBm • 11n HT20 MCS7 : -73 dBm • 11n HT40 MCS0 : -88 dBm • 11n HT40 MCS7 : -70 dBm 5 GHz : <ul style="list-style-type: none"> • 11a 6M : -97 dBm • 11a 54M : -79 dBm • 11ac VHT20 MCS0 : -96 dBm • 11ac VHT20 MCS11 : -66 dBm • 11ac VHT40 MCS0 : -94 dBm • 11ac VHT40 MCS11 : -63 dBm • 11ac VHT80 MCS0 : -91 dBm • 11ac VHT80 MCS11 : -60 dBm • 11ax HE20 MCS0 : -95 dBm • 11ax HE20 MCS11 : -63 dBm • 11ax HE40 MCS0 : -92 dBm • 11ax HE40 MCS11 : -60 dBm • 11ax HE80 MCS0 : -89 dBm • 11ax HE80 MCS11 : -58 dBm
DDNS	<ul style="list-style-type: none"> • No-IP • DynDNS • TP-LINK
DHCP server	✓
Firmware update	✓
Protections	WPA-PSK/WPA2-PSK DoS attacks protection, SPI network firewall, domain filtering, IP and MAC filtering, IP and MAC binding
Management interface	Web browser, TP-LINK Tether
Transmitter power	< 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz
Power supply	12 V DC / 1 A (power adapter included)



Main features	<ul style="list-style-type: none"> • Firewall • Internet access filtering • Static / dynamic routing • Built-in 4-port switch • Wireless transmission statistics • The WPS function allows to easy establish an encrypted connection • QoS • WMM (Wi-Fi Multimedia) • Rate limit • Access control • Remote management • DMZ • parental control • Guest Network - a separate and secure network for guests
Operation temp	0 °C ... 40 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)
Weight	0.44 kg
Dimensions	261 x 126 x 37 mm
Manufacturer / Brand	KLIMAS	KLIMAS	KLIMAS	TP-LINK
Guarantee	2 years	2 years	2 years	3 years

