

	EXPANSION PLUG KW-8/4X50 KLIMAS	ROUTER VPN TL-ER605 TP-LINK	EXPANSION PLUG KW-6/3.5X50 KLIMAS	TV OR MONITOR MOUNT BRATECK-PLB-CE344
				
	0.08 EUR 0.08 EUR	66.02 EUR 66.02 EUR	0.07 EUR 0.07 EUR	23.89 EUR 23.89 EUR
Material	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized 	...	<ul style="list-style-type: none"> Expansion plug, Polypropylene Screw, Steel galvanized 	...
Drilling diameter	8 mm	...	6 mm	...
Standards	...	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.1q
Expansion plug length	40 mm	...	30 mm	...
Mounting standard	VESA 75, 100, 200, 200x100, 400, 400x200
Screw dimensions	Ø 4 x 50 mm, PZ-2	...	Ø 3.5 x 50 mm, PZ-2	...
Screen size range	32 " ... 55 "
LAN ports	...	<ul style="list-style-type: none"> 2 x LAN 10/100/1000 Mbps (RJ-45) 2 x LAN/WAN 10/100/1000 Mbps (RJ-45)
Bearing capacity	50 kg
Application	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick 	...	<ul style="list-style-type: none"> Concrete Solid clay brick Solid sand-lime brick 	...
Distance from mounting surface	(manufacturer data) : 1050 ... 1560 mm from ceiling Our tests results : 920 ... 1510 mm from ceiling
WAN interface	...	<ul style="list-style-type: none"> 2 x LAN/WAN 10/100/1000 Mbps (RJ-45) 1 x WAN x 10/100/1000 Mbps (RJ-45) 1 x USB WAN - 3G/4G
Color	Black
Tilt adjustment	-15 ° ... 15 °
Horizontal rotation	360 °
Rotation in the plane of the screen	—
LED indicators	...	Power, System, WAN, LAN, USB
DDNS	...	<ul style="list-style-type: none"> DynDNS No-IP Peanuthull Comexe
DHCP server	...	✓
Port USB	...	USB 2.0
Firmware update	...	✓

Protections	...	<ul style="list-style-type: none"> • SPI network firewall • VPN Passthrough • FTP/H.323/PPTP/SIP/IPsec ALG <ul style="list-style-type: none"> • Support DoS defence • Support Ping of Death defence • URL addresses filtering • Support ARP defence • IP-MAC Binding • TCP/UDP/ICMP Flood network attacks protection • TCP (Stealth FIN/Xmas/Null) scan blocking • Ping packets blocking from WAN • Access control
Management interface	...	<ul style="list-style-type: none"> • Omada Central Management System • Software Omada Controller • Omada Hardware Controller • Remote management • Web browser
Main features	...	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, Open VPN, VPN Pass-through • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • MAC address cloning • DHCP client/server support • IPv6 compliance • IEEE 802.1Q VLAN • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • DMZ • IEEE 802.1x and Radius Authentication • SNMPv1/v2c/v3(MIB-2) • Reboot schedule • View topology and network status • RESET button
Power supply	...	12 V DC / 1 A (power adapter included)
Power consumption	...	max. 7.94 W
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Weight	...	0.374 kg	...	5.7 kg
Dimensions	...	158 x 101 x 25 mm	...	1080 x 520 x 60 mm



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Manufacturer / Brand	KLIMAS	TP-LINK	KLIMAS	...
Guarantee	2 years	5 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00