


	CABLE FOR SOLAR INSTALLATIONS H1Z2Z2-K-1X4.0/BK	CONNECTOR FOR LED STRIPS AD-TL-6499/Z-P/RGBW 12 mm ORNO	TV OR MONITOR MOUNT AX-MAGNUM	ROUTER RG-EG105G-P-V2. 4 PoE REYEE	ROUTER ER-X EdgeMAX UBIQUITI
					
	0.92 EUR 0.92 EUR	1.37 EUR 1.37 EUR	16.01 EUR 16.01 EUR	164.89 EUR 164.89 EUR	66.90 EUR 66.90 EUR
Mounting standard	VESA max. 600 x 400
Application	...	Works with LED lighting RGBW
Number of power outputs	...	2 pcs
Processor	Dual-Core 880 MHz, MIPS1004Kc
Screen size range	32 " ... 65 "
Strip width	...	12 mm
Bearing capacity	30 kg
Length of the cable	...	140 mm
Distance from mounting surface	58 mm
Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at	IEEE 802.3ad, IEEE 802.1q
"Index of Protection"	...	—
Maximal power voltage	...	48 V
Inner conductor	4.0 mm ² - Stranded wire Cu - Tin-plated
Color	...	White	Black
Tilt adjustment	-15 ° ... 5 °
Horizontal rotation	—
Rotation in the plane of the screen	—
Rated voltage	600 V / 1000 V AC 1800 V DC
LAN ports	• 3 x LAN & PoE 10/100/1000 Mbps (RJ-45) • 1 x LAN & PoE / WAN 10/100/1000 Mbps (RJ-45)	5 x LAN 10/100/1000 Mbps (RJ-45)
Outer coating	Ø 5.0 mm - Non-halogen plastic
WAN interface	• 1 x WAN x 10/100/1000 Mbps (RJ-45)	configurable
LED indicators	Status, Link/Act	Power, LAN
DDNS	✓	✓
DHCP server	✓	✓
Port USB	—	...
Firmware update	✓	...
Coating color	Black
Protections	• ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping	• NAT network firewall • LAN ACL • Contact/Air (ESD/EMP) : ± 24 kV / ± 24 kV
Management interface	• Ruijie Cloud Central Management System • Configuration using the Ruijie Reye application • Remote management • Web browser	• Software EdgeOS, Software PC • Remote management • Web browser

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile phones support	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee	...
Power supply PoE	Power output - LAN ports : PoE (802.3af/at) max. 54 W (total)	Ubiquiti Passive PoE
Housing	...	Plastic	Metal
Main features	<ul style="list-style-type: none"> • UV radiation resistance • Ozone resistance • Hydrolysis resistance • Resistant to oils and aggressive chemicals • Flame resistance (according to VDE 0482-332-2, DIN EN 60332-1) • The insulating layer is made of halogen-free material, which does not produce aggressive fumes during combustion • Increased mechanical strength of the outer coating • Expected lifetime : 25 years 	...	In the kit : Expansion plugs Ø 8 x 50 mm	<ul style="list-style-type: none"> • VPN networks: IPsec VPN, Open VPN, LZTP VPN, PPTP VPN, etc. • Static / dynamic routing • WAN : PPPoE, PPTP, LZTP • DHCP client/server support • Access Control List - ACL package filtering based on source and destination IP addresses • Rate limit • Load balance • NAT • View topology and network status • RESET button 	<ul style="list-style-type: none"> • IEEE 802.1Q VLAN • PPPoE • Static routing • DHCP • IPv6 compliance • IGMP • NAT • VPN networks: IPsec VPN, LZTP VPN, PPTP VPN, Open VPN • Dynamic DNS • Client - Radius support • QoS - mechanisms, which provide the high quality of transmission • Switch is managed via a web browser, command line interface and SNMP, NetFlow, LLDP, NTP, UBNT Discovery Protocol protocols • View topology and network status • RESET button • Possible power supply via Passive PoE via eth4/Poe OUT port - 24 V ("+" : 4, 5 pins; "-" : 7, 8 pins) • Possibility to mount to the wall
Power supply	54 V DC / 1.15 A (power adapter included)	<ul style="list-style-type: none"> • 12 V DC / 0.5 A (power adapter included) • Passive PoE 24 V - port eth0/PoE IN
Power consumption	max. 60 W (at full load)	max. 5 W
Operation temp	0 °C ... 40 °C	-10 °C ... 45 °C
Permissible relative humidity	10 % ... 90 % (non-condensing)	10 % ... 90 % (non-condensing)
Weight	...	0.002 kg	1.27 kg	0.43 kg	0.172 kg
Dimensions	...	140 x 15 x 5 mm	640 x 420 x 50 mm	207 x 109 x 28 mm	110 x 75 x 22 mm
Manufacturer / Brand	...	ORNO	...	RUIJIE / REYEE	UBIQUITI
Guarantee	2 years	2 years	2 years	2 years	2 years