



	<a href="#">WI-FI SMART PLUG ATLO-P1-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">NVR TC-R3105 SPEC:1/B/P4/K/V3.1 5 CHANNELS, 4 PoE TIANDY</a>
		
	7.11 EUR 7.11 EUR	418.77 EUR 418.77 EUR
Standard	...	IP
Rated voltage	100 ... 240 V	...
Supported resolutions	...	max. 8 Mpx
Maximal total load	3680 W	...
Total maximal current	16 A	...
Video outputs	...	1 pcs HDMI 4K 1 pcs VGA
Number of outlets	1 pcs	...
Audio support	...	5 Channels - Audio from cameras
Socket type	CEE 7/3 (Schuko)	...
Audio inputs	...	1 pcs
Plug type	CEE 7/7	...
Audio outputs	...	1 pcs
Grounding	✓	...
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Image compression method	...	S+265 / H.265 / S+264 / H.264
Supported hard drives	...	1 x 10 TB SATA
Recording modes	...	Manual, Motion Detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4 channel synchronous playback
Main features	<ul style="list-style-type: none"> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control</li> <li>• Energy measurement</li> <li>• ON/OFF button</li> <li>• STATUS indicator</li> </ul>	...
Housing	Plastic	...
Color	White	...

Operation temp	-20 °C ... 50 °C	...
Permissible relative humidity	≤ 80 %	...
Network interface	...	1 x RJ-45 - 10 / 100 Mbps
Network functions	...	Full support via network, Remote records copying, Web-Server built-in
ONVIF	...	✓
Bitrate	...	max. 80 Mbps
Default admin user / password	...	admin / - The administrator password should be set at the first start
Default IP address	...	192.168.1.3
RTSP URL	...	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream
Web browser access ports	...	80, 433, 3000, 3001, 3002, 23002
PC client access ports	...	3000, 3001
Mobile client access ports	...	3000, 3001
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EasyLive Plus</a></li> <li>• iOS (iPhone): Free application <a href="#">EasyLive Plus</a></li> </ul>
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application <a href="#">Easy7 Smart Client Express</a>
Alarm inputs / outputs	...	4 / 1
PTZ control	...	✓
Motion Detection	...	✓
Intelligent image analysis	...	—
USB	...	2 x USB 2.0
Mouse support	...	✓
IR remote controller in the set	...	—

Main features	...	Support for Intelligent Image Analysis function, available in TIANDY cameras : <ul style="list-style-type: none"> <li>• crossing the line (tripwire)</li> <li>• double crossing the line</li> <li>• abandoned/missing object</li> <li>• detection of loitering in a given area</li> <li>• running</li> <li>• parking detection</li> <li>• detection of people gathering</li> <li>• protective helmet detection</li> <li>• detection of persons on duty</li> <li>• signal loss indication</li> <li>• detection of persons on duty</li> <li>• people counting</li> <li>• face detection</li> </ul>
Switch PoE	...	4-port PoE Switch built-in, 30 W / Channel - PoE
Maximum total switch load	...	45 W
Power supply	...	48 V DC / 1.35 A (power adapter included)
Weight	0.08 kg	0.91 kg
Dimensions	50 x 50 x 83 mm	255 x 240 x 45 mm
Supported languages	...	Polish, English, Albanian, Arabic, Spanish, Korean, French, Hebrew, Dutch, Portuguese, German, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	...	TIANDY
Guarantee	2 years	3 years