





	<a href="#">SMART LED LIGHTING CONTROLLER ATLO-SW1-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">SMART SWITCH WITH TEMPERATURE MEASUREMENT ATLO-TS1-TUYA Wi-Fi, Tuya Smart</a>	<a href="#">ADAPTER AD-UTP-2W/2G 2 x RJ45</a>	<a href="#">USB 3.0 ETHERNET NETWORK ADAPTER TL-UE306 TP-LINK</a>
				
	7.28 EUR 7.28 EUR	13.27 EUR 13.27 EUR	5.63 EUR 5.63 EUR	14.32 EUR 14.32 EUR
Supported standards	...	...	...	Gigabit Ethernet
Chipset	...	...	...	AX88179
Application	switching devices on/off	<ul style="list-style-type: none"> <li>• Temperature measurement</li> <li>• switching devices on/off</li> </ul>	...	...
Number of channels	1	...	...	...
Supported transmission speeds	...	...	...	10 / 100 / 1000 Mbps
Interface	...	...	...	USB 3.0
Connectors type	...	...	<ul style="list-style-type: none"> <li>• 1 Adapter : 2 x RJ-45 plug + 1 x RJ-45 socket</li> <li>• 2 Adapter : 3 x RJ-45 socket</li> </ul>	...
Length of the cable	...	...	3 cm	...
Power supply	100 ... 240 V AC, 50 / 60 Hz	85 ... 250 V	...	...
Ports	...	...	...	<ul style="list-style-type: none"> <li>• 1 x RJ45,</li> <li>• 1 x USB 3.0 - A type</li> </ul>
Temperature measurement	...	-50 °C ... 125 °C ± 0.5 °C	...	...
Operating system	...	...	...	Windows 7 / 8 / 8.1 / 10, Linux
Main features	...	...	...	<ul style="list-style-type: none"> <li>• Compact folding design</li> <li>• Plug &amp; Play</li> </ul>
Maximal total load	250 W	3000 W	...	...
Certificates	...	...	...	CE, FCC
Total maximal current	10 A	16 A	...	...
Number of inputs	1	1	...	...
Number of outputs	1	1	...	...
Radio communication range	< 100 m (open area)	...	...	...
Connector type	screw terminals	screw terminals	...	...
Manufacturer / Brand	...	...	...	TP-LINK
Wireless	<ul style="list-style-type: none"> <li>• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n</li> <li>• Bluetooth</li> </ul>	<ul style="list-style-type: none"> <li>• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n</li> <li>• Bluetooth</li> </ul>	...	...
Mobile phones support	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	<ul style="list-style-type: none"> <li>• The <a href="#">Tuya Smart</a> free application on Android</li> <li>• The <a href="#">Tuya Smart</a> free application on iOS</li> </ul>	...	...
"Index of Protection"	IP20	...	...	...

Main features	<ul style="list-style-type: none"> <li>• Local control by physical button ,</li> <li>Tuya Smart :</li> <li>• schedule,</li> <li>• timer,</li> <li>• Setting scenarios by different events,</li> <li>• remote access,</li> <li>• voice control ,</li> </ul>	<ul style="list-style-type: none"> <li>• Temperature Sensor : DS18B20 - Measuring accuracy <math>\pm 0.5 \text{ }^\circ\text{C}</math> @ <math>-10 \text{ }^\circ\text{C}</math> ... <math>85 \text{ }^\circ\text{C}</math></li> <li>• Warning indication about exceeding the preset temperature,</li> <li>• schedule,</li> <li>• timer,</li> <li>• remote access,</li> <li>• voice control,</li> <li>• Pairing button,</li> <li>• Wi-Fi indicator,</li> <li>• Temperature history graph,</li> <li>• Settings memory after power failure,</li> <li>• Energy measurement, energy consumption history graph,</li> <li>• For indoor use</li> </ul>	...	...
Housing	Plastic	Plastic	...	...
Color	White	White	...	...
Operation temp	$-10 \text{ }^\circ\text{C}$ ... $40 \text{ }^\circ\text{C}$	$0 \text{ }^\circ\text{C}$ ... $40 \text{ }^\circ\text{C}$	...	...
Permissible relative humidity	...	5 % ... 90 % (non-condensing)	...	...
Weight	0.03 kg	0.1 kg (total)	0.05 kg (total)	0.03 kg
Dimensions	43 x 39 x 22 mm	<ul style="list-style-type: none"> <li>• 93 x 55 x 30 mm</li> <li>• 95 cm (cable length) - Probe</li> </ul>	<ul style="list-style-type: none"> <li>• 1 Adapter : 115 x 19 x 19 mm</li> <li>• 2 Adapter : 120 x 40</li> </ul>	<ul style="list-style-type: none"> <li>• 71 x 26 x 16 mm</li> <li>• Length of the cable : 11 cm</li> </ul>
Guarantee	2 years	2 years	2 years	2 years