



	ACCESS CONTROLLER DHI-ASC1202B-D DAHUA	SWITCH POE CS4010-8GT-110 8-PORT DAHUA
		
	142.63 CHF 142.63 CHF	264.99 CHF 264.99 CHF
Support	DAHUA	...
Number of supported readers	4 pcs	...
Battery backup support	—	...
Input lines	8	...
Output lines	6 pcs (4 pcs Relay)	...
LAN ports	...	<ul style="list-style-type: none"> • 8 x RJ45 10/100/1000 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Communication	<ul style="list-style-type: none"> • RS-485, • Ethernet, • Wiegand 34/26 	...
Transmission speed	...	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 : 2 Uplink ports
Maximal output power	...	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports
Maximal total power	...	110 W
MAC addresses table	...	8k
Management	...	✓
Permissible relative humidity	max. 95 % (non-condensing)	...
Operation modes	...	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6
LED diodes	...	Power, System, PoE, Link/Act

Main features	<ul style="list-style-type: none"> • 100000 indexed users • History of 150000 events • Remote programming from PC • Watchdog built-in • Possibility to mount on a wall, or on the DIN TS-35 rail 	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Possibility to mount to the wall
Certificates	...	CE
Protections	...	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV
Housing	...	Desktop, Metal
Power supply	9 ... 15 V / 500 mA DC	54 V DC / 2.22 A (power adapter included)
Power consumption	...	max. 110 W
Operation temp	-30 °C ... 60 °C	-10 °C ... 55 °C
Weight	0.388 kg	0.52 kg
Dimensions	206 x 117 x 51 mm	190 x 106 x 30 mm
Manufacturer / Brand	DAHUA	DAHUA
Guarantee	3 years	3 years