



	SWITCH POE CS4010-8GT-110 8-PORT DAHUA	SWITCH POE IPB-5-10A-S4 5-PORT ATTE
		
	270.93 EUR 270.93 EUR	78.14 EUR 78.14 EUR
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 10/100/1000 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink 	<ul style="list-style-type: none"> • 1 x RJ45 10/100 Base-T - Uplink • 5 x RJ45 10/100 Base-T - PoE (802.3af/at) / Passive PoE
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 : 2 Uplink ports 	10 / 100 Mbps : 1 Port LAN + 5 LAN & PoE ports
MAC addresses table	8k	...
Management	✓	—
Maximal output power	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports 	<ul style="list-style-type: none"> • 40 W @ Passive PoE - 1 ... 5 ports, • 30 W @ PoE (802.3at) - 1 ... 5 ports • 15.4 W @ PoE (802.3af) - 1 ... 5 ports
Operation modes	Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6	...
Maximal total power	110 W	90 W
LED diodes	Power, System, PoE, Link/Act	Power, LAN

Main features	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Loop Protection • Compliance with the LLDP protocol • Spanning Tree STP/RSTP • Port Based VLAN : 32 • Data Flow Control (802.3x) • DHCP client • RESET button • Possibility to mount to the wall 	<ul style="list-style-type: none"> • Supported PoE devices: 802.3af/at, Passive PoE • Possibility to connecting in cascade • Efficiency : 93 % @ 90 W • 5 polymer fuses - PoE • Possibility to power other devices powered from 55 V (screw connection) • PSU thermal protection • Short-circuit protection • Overload protection • The ability to independently turn on and off the PoE power for each of the LAN 1 ... LAN 4 ports • Switch has built-in a 55 V DC power supply adapter with power of 90 W • "Index of Protection" : IP55
Certificates	CE	...
Protections	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV 	...
Housing	Desktop, Metal	...
Power supply	54 V DC / 2.22 A (power adapter included)	180 ... 240 V AC - Built-in switching power supply
Power consumption	max. 110 W	...
Operation temp	-10 °C ... 55 °C	...
Weight	0.52 kg	0.43 kg
Dimensions	190 x 106 x 30 mm	158 x 118 x 77 mm
Manufacturer / Brand	DAHUA	ATTE
Guarantee	3 years	3 years