



	IP SPEED DOME CAMERA OUTDOOR DS-2DE5425IW-AE(T5) - 3.7 Mpx 4.8 ... 120 mm Hikvision	TV OR MONITOR MOUNT BRATECK-KL22-22F
		
	977.38 EUR 977.38 EUR	8.75 EUR 8.75 EUR
Standard	TCP/IP	...
Sensor	1/2.8 " Progressive Scan CMOS	...
Matrix size	4 Mpx	...
Mounting standard	...	VESA : 50, 75, 100, 200 x 100, 200
Screen size range	...	23 " ... 42 "
Bearing capacity	...	35 kg
Distance from mounting surface	...	19.5 mm
Tilt adjustment	...	—
Horizontal rotation	...	—
Rotation in the plane of the screen	...	—
Resolution	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	...
Scanning system	Progressive	...
Lens	4.8 ... 120 mm	...
View angle	• 55 ° ... 2.4 ° (manufacturer data) • 52 ° ... 3.2 ° (our tests result)	...
Optical zoom	x 25	...
Digital zoom	x 16	...
Range of IR illumination	150 m	...
Video output	—	...
Preset rotation speed	120 °/s (horizontal) 80 °/s (vertical)	...
Rotation speed (manual control)	0.1 °/s ... 120 °/s (horizontal) 0.1 °/s ... 80 °/s (vertical)	...
Horizontal rotation range	360 ° - continuous	...
Vertical rotation range	-15 ° ... 90 °	...
RS-485 interface	—	...
Number of presets	300	...
Horizontal scan	✓	...
Route settings	8	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...
Alarm inputs / outputs	2 / 1	...

Audio	<ul style="list-style-type: none"> • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection • Digital Noise Reduction 	...
Main stream frame rate	25 fps @ 3.7 Mpx	...
Network interface	10/100 Base-TX (RJ-45)	...
Network protocols	IPv4/IPv6, HTTP, HTTPS, IEEE 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, WebSocket, WebSockets	...
WEB Server	Built-in	...
Max. number of on-line users	20	...
ONVIF	19.12	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Mobile phones support	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Hik-Connect • iOS: Free application Hik-Connect 	...
Default admin user / password	admin / - The administrator password should be set at the first start	...
Default IP address	192.168.1.64	...
Web browser access ports	80	...
PC client access ports	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application	...
Mobile client access ports	8000	...
Port ONVIF	80	...
RTSP URL	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ <ul style="list-style-type: none"> • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/	...



Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Intelligent 3D Positioning System • Day/Night mode (color/b&w/auto) • ICR - Movable InfraRed filter • Auto White Balance • Privacy zones - max. 24 • Motion Detection • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • The function of setting the exposure for a given area • The function of setting the focus for a given area • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support • Parking action - this function enables to locate the camera to specific position automatically if operator doesn't operate the controller for some time • The camera is equipped with a built-in heater with a thermostat • Camera from AcuSense series • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, classification of people and vehicles, video tampering, abandoned/missing object, face detection - advanced face capture features - detection of up to 5 faces simultaneously 	...
Power supply	<ul style="list-style-type: none"> • PoE (802.3at), • 24 V AC / 2.5 A (power adapter included) 	...
Power consumption	≤ 24 W	...
Housing	Speed Dome, Metal + Plastic	...
Color	White + Black	Black
Operation temp	-30 °C ... 65 °C	...
"Index of Protection"	IP66	...
Weight	<ul style="list-style-type: none"> • 3.7 kg (without bracket) • 4.7 kg (with bracket) 	0.422 kg
Dimensions	Ø 210 x 345 mm (without bracket) 420 x 208 x 379 mm (with bracket)	265 x 222 x 19.5 mm
Supported languages	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Vietnamese, Italian	...
Manufacturer / Brand	Hikvision	BRATECK
SAP Code	327000458	...
Guarantee	3 years	2 years