



	EXTENDER EXT-POE4H IN A HERMETIC CASING PULSAR	CIRCUIT BREAKER LE-419203 ONE-PHASE 20 A C TYPE LEGRAND
		
	67.33 AUD 67.33 AUD	6.14 AUD 6.14 AUD
Input voltage	42 ... 57 V DC	...
Device type	...	Circuit Breaker, One-phase
Output voltage	42 ... 57 V DC	...
Rated current	...	20 A
Number of inputs	1	...
Number of poles	...	1
Tripping curves	...	C type
Number of outputs	2	...
Breaking capacity	...	6000 A
Connector	3 x RJ-45 socket	...
LED indicators	Link/Act	...
Rated voltage	...	<ul style="list-style-type: none"> • 230 V AC / 50 Hz • 400 V AC / 50 Hz
Connectors type	...	screw terminals
Width in 17.5 mm modules	...	1
Supported data rates	<ul style="list-style-type: none"> • Range : 100 m - Input, 100 m - 2 x Output, • Supported data rates 10 / 100 Mbps - Fast Ethernet 	...
Output power	max. 14.4 W / port PoE , max. 20 W (total)	...
Protections	<ul style="list-style-type: none"> • Overvoltage • Overload • Short-circuit 	...
Housing	Plastic, hermetic	Plastic, DIN, TS-35 rail mounting
"Index of Protection"	IP56	...
Operation temp. / Relative humidity	-10 ... 40 °C / 10 ... 90 %	...
Weight	0.55 kg	0.128 kg
Dimensions	198 x 148 x 80 mm	83 x 74 x 17.5 mm
Manufacturer / Brand	PULSAR	LEGRAND
Guarantee	2 years	2 years