

	UPS AT-UPS1500-LED 1500 VA EAST	EXTENDER HDMI-EX-4	MOUNT RACK FRAME U19-4U/340
			
	141.96 EUR 141.96 EUR	48.03 EUR 48.03 EUR	23.89 EUR 23.89 EUR
Nominal power	900 W
Color	Black (RAL 9005)
Apparent Power	1500 VA
Internal depth	330 mm
Input voltage	230 V AC \pm 25 %
Input frequency	50 / 60 Hz (auto detection)
Supported HDMI resolutions	...	1080p, 1080i, 720p, 576p, 576i, 480p, 480i	...
Output voltage	230 V AC \pm 10 % (Approximated Sine Wave)
Output frequency	50 / 60 Hz \pm 1 %
Voltage adjustment	—
Frequency adjustment	—
Transfer time	2 ... 7 ms (typical), max. 10 ms
Charging time (recover to 90% capacity)	6 ... 8 hours
Maximal transmission range	...	<ul style="list-style-type: none"> • 40 m @ 720p / 1080p - UTP cat. 6 (manufacturer data) • 60 m @ 1080p - UTP cat. 6 (our tests result) • 50 m @ 1080p - UTP cat. 5e (our tests result) 	...
Battery	2 pcs - 12V/8Ah
Supported audio formats	...	DTS-HD, Dolby true HD, LPCM7.1, AC3, DTS, DSD	...
Power supply	...	5 V DC / 1000 mA - 2 pcs of power adapters included	...
Operation temp	...	-10 °C ... 55 °C	...
Permissible relative humidity	...	5 % ... 90 %	...
Estimated battery operation time	<ul style="list-style-type: none"> • 35 minutes @ 100 W, • 17.5 minutes @ 200 W, • 11.5 minutes @ 300 W, • 4 minutes @ 500 W, • 1.5 minutes @ 800 W
Number of outputs	3 pcs CEE 7/3 (Schuko)

Management software	UPSmart (Windows 95/98/2000/XP/Vista/7/8/10, Linux)
Protections	<ul style="list-style-type: none"> • Fuse • Short-circuit • Overload • Overvoltage - RJ45 • Overcharge protection • discharge protection • Output voltage filtering • DC filter to eliminate interferences - EMI/RFI
Operation state indication	<ul style="list-style-type: none"> • LED diodes, • Sound signaling
Main features	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Excellent microprocessor control guarantees high reliability • COLD START function for manual switch to the battery power supply • Automatic Voltage Regulator (AVR) • Automatic battery charging in OFF mode • self test feature • 2 x RJ45 - Input / Output • Port USB 2.0 - Access from PC • Remote management - UPSmart application (included) • Configurable alarm • Built-in EMI, RFI filter • The device works with power supply adapters having Active Power Factor Correction (APFC)
Application	<ul style="list-style-type: none"> • network, servers, workstations • Surveillance Systems • small servers, DVRs, telecommunication equipment, VoIP working hardware, desktop computers, etc.
Housing type	Tower
Operation temp. / Relative humidity	0 °C ... 40 °C / 20 ... 90 %
Weight	9.55 kg	0.045 kg	2.71 kg
Dimensions	348 x 140 x 173 mm	67 x 56 x 22 mm	500 x 151 x 331 mm - RACK 19 " x 4 U

Manufacturer / Brand	EAST
Guarantee	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00