





	CIRCUIT TESTER ST-STHT0-62685 STANLEY	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HFW2802TU-Z-A-27135-S2-DIP 2.7 ... 13.5 mm - MOTOZOOM DAHUA	WIRELESS GLASS BREAK DETECTOR AGD-200-DG (Glass-Break-Detector-DG) SATEL	PERFORATED MOUNTING RAIL TS-35
				
	2.67 USD 2.67 USD	346.42 USD 346.42 USD	66.65 USD 66.65 USD	2.05 USD 2.05 USD
Length	1 m
Detection	detection of breaking plate, laminated or tempered glass	...
Material	Steel galvanized
AC voltage range	125 V ... 250 V
Support	Satel ABAX/ABAX2	...
Alarm signaling	Signal to control panel	...
Standard	...	AHD / HD-CVI / HD-TVI / PAL
Working frequency band	50 Hz ... 500 Hz
Frequency band	868 MHz ... 868.6 MHz	...
Matrix size	...	8.3 Mpx
Tip width	3.5 mm
Arrowhead length	105 mm
Radio communication range (at open area)	~ 500 m @ ABAX , ~ 2000 m @ ABAX2	...
Battery	CR123A 3 V - 3.0 V (included)	...
Backup time	~ 2 years	...
Main features	<ul style="list-style-type: none"> • Wide range of voltage detection • Neon indicator light 	...	<ul style="list-style-type: none"> • advanced dual-path microprocessor signal analysis • Remote configuration • Tamper protections 	Perforated
Operation temp	-10 °C ... 55 °C	...
Resolution	...	3840 x 2160 - 8.3 Mpx @ HD-CVI / HD-TVI / AHD @ 15 fps , 2592 x 1944 - 5 Mpx @ HD-CVI @ 25 fps , 2560 x 1440 - 3.7 Mpx @ HD-CVI @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps
Sensor	...	Progressive Scan CMOS
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Lens	...	2.7 ... 13.5 mm - Motozoom
View angle	...	113 ° ... 47 °
Range of IR illumination	...	80 m
IR illuminator power adjustment	...	Automatic
Audio	...	Microphone built-in Audio support via coaxial cable - HD-CVI only

Main features	...	<ul style="list-style-type: none"> • Motozoom lens, AutoFocus • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC/HLC-Pro - Back Light / High Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Day/night mode • ICR - Movable InfraRed filter • Configurable Privacy Zones • F-DNR (Defog) - Reduction of image noise caused by precipitation • Mirror - Mirror image • Sharpness - sharper image outlines • D-ZOOM - Digital Zoom : 4 x
OSD menu	...	✓
Power supply	...	12 V DC / 1.16 A
Power consumption	...	≤ 13.9 W
Housing	...	Compact, Metal
Color	...	White + Black	Dark graphite	...
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Weight	0.028 kg	0.78 kg	0.02 kg	0.3 kg
Dimensions	Ø 18 x 190 mm	244 x 90 x 90 mm	20 x 102 x 23 mm	1000 x 35 x 7.5 mm
Manufacturer / Brand	STANLEY	DAHUA	SATEL	...
Guarantee	2 years	3 years	2 years	2 years