



	SWITCH POE GTX-B1-10-82G 8-PORT	MAINS SOCKET TESTER UT-07A-EU UNI-T
		
	1759.81 CZK 1759.81 CZK	167.12 CZK 167.12 CZK
Rated voltage	...	230 V AC
LAN ports	<ul style="list-style-type: none"> • 8 x RJ45 (1 x Hi-PoE + 7 x PoE (802.3af/at)), • 2 x RJ45 - Uplink 	...
"Index of Protection"	...	IP40
Manufacturer / Brand	...	UNI-T
Management	—	...
LED diodes	Power, V - VLAN (Port Isolation), S - Extend, PoE, Link/Act, Speed	...
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink, • 10 / 100 Mbps : 8 x Port LAN & PoE 	...
Operation modes	<ul style="list-style-type: none"> • N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps 	...
Maximal output power	<ul style="list-style-type: none"> • 60 W / port Hi-PoE - Port 1 • 30 W / port PoE - 2 ... 8 ports 	...
Maximal total power	120 W	...
MAC addresses table	2k	...

Main features	<ul style="list-style-type: none"> • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Full Duplex: IEEE802.3x, Half Duplex: Back Pressure • Auto-learning and Auto-aging functions support for MAC addresses • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • MTBF (Mean Time Between Faults) : 50000 h 	<ul style="list-style-type: none"> • Phase conductor position test • Signaling a lack of grounding • Signaling phase failure • Signaling a lack of a neutral wire • Signaling of phase and ground swap • Signaling of phase and ground swap and a lack of grounding
Certificates	CE, FCC Class B	...
Protections	Overvoltage \pm 4 kV	...
Power supply	100 ... 265 V AC	...
Operation temp	-10 °C ... 45 °C	0 °C ... 40 °C
Weight	0.77 kg	0.08 kg
Dimensions	210 x 150 x 35 mm	65 x 65 x 72 mm
Guarantee	2 years	2 years