




	MECHANICAL SPLICE WITH SC CONNECTOR FAST-SC OPTON	POWER DISTRIBUTION UNIT PR-1.5M-6G-SW/W (6 OUTLETS) 1.3 m	POWER DISTRIBUTION UNIT LE-049484 (6 OUTLETS) 1.5 m LEGRAND
			
	1.43 CAD 1.43 CAD	8.20 CAD 8.20 CAD	24.30 CAD 24.30 CAD
Fiber type	Single-mode
Connector type	SC/UPC
Fiber diameter	125 µm
Rated voltage	...	220 ... 240 V AC / 50 Hz	230 V AC / 50 Hz
Total maximal current	...	10 A	16 A
Maximal total load	...	2500 W	3680 W
Cable diameter	3 mm / 2 mm / 900 µm / 250 µm
Number of outlets	...	6 grounded outlets 10A/250V CEE 7/5	6 grounded outlets 16A/250V CEE 7/5
Fuse	...	—	—
Switch	...	✓	—
Wire gauge	...	3 x 1.5 mm ²	3 x 1.0 mm ²
Length of the cable	...	1.3 m	1.5 m
Splice reuse	max. 5 times
Housing	...	Plastic	Plastic
Color	...	White	White / Gray
Weight	...	0.4 kg	0.39 kg
Dimensions	...	313 x 54 x 46 mm	295 x 54 x 37 mm
Manufacturer / Brand	OPTON	...	LEGRAND
Guarantee	2 years	2 years	2 years