




	<a href="#">IP SPEED DOME CAMERA OUTDOOR IPC675LFW-AX4DUPKC-VG - 5 Mpx 2.8 ... 12 mm UNIVIEW</a>	<a href="#">AHD, HD-CVI, HD-TVI, PAL CAMERA DS-2CE76D0T-ITPF(2.8MM)(C) - 1080p Hikvision</a>
		
	465.88 EUR 465.88 EUR	41.78 EUR 41.78 EUR
Standard	TCP/IP	AHD / HD-CVI / HD-TVI / CVBS
Sensor	1/2.7 " Progressive Scan CMOS	Progressive Scan CMOS
Matrix size	5 Mpx	2.1 Mpx
Resolution	2880 x 1620 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	<ul style="list-style-type: none"> <li>• 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI - 25 fps</li> <li>• 960 x 576 - 960H @ PAL</li> </ul>
IR illuminator power adjustment	...	Automatic
Lens	2.8 ... 12 mm	2.8 mm
IR illuminator support	...	ICR - Movable InfraRed filter
View angle	<ul style="list-style-type: none"> <li>• 104 ° ... 31 ° (manufacturer data)</li> <li>• 81 ° ... 30 ° (our tests result)</li> </ul>	<ul style="list-style-type: none"> <li>• 101 ° (manufacturer data)</li> <li>• 96 ° (our tests result)</li> </ul>
Optical zoom	x 4	...
Digital zoom	—	...
Range of IR illumination	50 m	20 m
White light LED illuminator range	10 m	...
Video output	—	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Preset rotation speed	<ul style="list-style-type: none"> <li>• 50 °/s (horizontal)</li> <li>• 40 °/s (vertical)</li> </ul>	...
Rotation speed (manual control)	<ul style="list-style-type: none"> <li>• 0.1 °/s ... 50 °/s (horizontal),</li> <li>• 0.1 °/s ... 40 °/s (vertical)</li> </ul>	...
OSD menu	...	OSD menu available via recorder
Horizontal rotation range	0 ° ... 345 ° - Rotation of the head is limited by stops	...
Vertical rotation range	-10 ° ... 110 °	...
RS-485 interface	—	...
Number of presets	256	...
Horizontal scan	—	...
Route settings	16	...
Image compression method	Ultra H.265 / H.265 / H.264 / MJPEG	...
Alarm inputs / outputs	—	...

SAP Code	...	300613699
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in</li> <li>• Bi-directional audio streaming support</li> <li>• Audio detection</li> <li>• Noise reduction</li> </ul>	...
Main stream frame rate	25 fps @ 5 Mpx	...
Network interface	10/100 Base-TX (RJ-45)	...
Network protocols	IPv4, IGMP, ICMP, ARP, TCP/IP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, SSL	...
WEB Server	Built-in	...
Max. number of on-line users	32	...
ONVIF	✓	...
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)	...
Mobile phones support	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>	...
Default IP address	DHCP or 192.168.1.13	...
Default admin user / password	admin / 123456	...
Web browser access ports	80, 554	...
PC client access ports	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>	...
Mobile client access ports	80	...
Port ONVIF	80	...
RTSP URL	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream	...



Main features	<ul style="list-style-type: none"> <li>• Intelligent Object Tracking</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• Support ARP defence</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• Day/night mode</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• RESET button - on the cable</li> <li>• Privacy zones - max. 4</li> <li>• Motion Detection</li> <li>• Tamper signaling</li> <li>• Image rotation and mirror</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network</li> <li>• Home Position - set the camera to the specified position if no operator activity for a specified dwell time</li> <li>• Active deterrence function - Active intrusion deterrence works by blinking blue and red light and siren sound or voice prompts</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, people counting, crowd gathering estimation, face detection</li> </ul>	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 2D-DNR - Digital Noise Reduction</li> <li>• EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners</li> <li>• AGC - Automatic Gain Control</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• Sharpness - sharper image outlines</li> </ul>
Housing	Speed Dome, Plastic	Dome, Plastic
Color	White + Black	White
"Index of Protection"	IP66	—
Vandal-proof	—	—
Power supply	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 1.5 A</li> </ul>	12 V DC / 190 mA
Power consumption	≤ 18 W	≤ 2.2 W
Operation temp	-20 °C ... 60 °C	-40 °C ... 60 °C
Weight	0.94 kg	0.14 kg
Dimensions	Ø 133 x 185 x 276 mm (without bracket)	Ø 85 x 79 mm

Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian	...
Manufacturer / Brand	UNIVIEW	Hikvision
Guarantee	2 years	3 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00