



	<a href="#">BATTERY 12V/12AH-MWS</a>	<a href="#">ACCESS POINT +ROUTER ARCHER-VR400 VDSL / ADSL 300 Mbps + 867 Mbps</a>
		
	20.52 EUR 20.52 EUR	80.83 EUR 80.83 EUR
Battery capacity	12 Ah	...
Rated voltage	12 V	...
Battery charging current	max. 4 A	...
Frequency range	...	<ul style="list-style-type: none"> <li>• 2.4 GHz,</li> <li>• 5 GHz</li> </ul>
Battery type	Maintenance-free AGM (Absorbent Glass Mat) battery	...
Connector	T1 type	...
Battery lifetime	3 ... 5 years	...
Standards	...	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
LAN ports	...	3x RJ-45 ( 10/100 Mbps, Auto MDI/MDX ) 1x RJ-45 ( 10/100/1000 Mbps, Auto MDI/MDX )
WAN interface	...	1x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2
Transmitter power	...	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Baud rates	...	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz
DHCP server	...	✓
Firmware update	...	✓
DDNS	...	✓

Protections	...	<ul style="list-style-type: none"> <li>• LAN : Firewall, MAC addresses filtering, IP addresses filtering, parental control, LAN ACL</li> <li>• WLAN : WEP 64/128-bit, WPA-PSK/WPA2-PSK, TKIP/AES</li> </ul>
Management interface	...	Web browser
Main features	...	<ul style="list-style-type: none"> <li>• Firewall</li> <li>• Internet access filtering</li> <li>• Static / dynamic routing</li> <li>• Built-in 4-port switch</li> <li>• Wireless transmission statistics</li> <li>• The WPS function allows to easy establish an encrypted connection</li> <li>• QoS</li> <li>• WMM (Wi-Fi Multimedia)</li> <li>• Rate limit</li> <li>• Access control</li> <li>• Remote management</li> <li>• DMZ</li> <li>• parental control</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• 1 x Port USB 2.0</li> <li>• The DSL line splitter included</li> </ul>
Operation temp	...	0 °C ... 40 °C
Permissible relative humidity	...	max. 90 % (max)
Power supply	...	12 V DC / 1.5 A (power adapter included)
Weight	3.25 kg	0.32 kg
Dimensions	151 x 98 x 95 mm	216 x 125 x 32 mm
Manufacturer / Brand	...	TP-LINK
Guarantee	2 years	2 years