







	VANDALPROOF CAMERA DP-954HHD/IRD STANDARD: PAL, 1000 TVL 2.8 mm	TV OR MONITOR MOUNT AX-TYTAN-ALUX	TOGGLE PLUG DUOTEC-10/SPH Fischer	TV OR MONITOR MOUNT BRATECK-LPA68-221	DOOR FOR 96-MODULAR DISTRIBUTION CABINETS LE-337254 XL ³ S 160 LEGRAND	DIGITAL TIMER OR- PRE-409 ORNO
						
	49.11 EUR 49.11 EUR	105.52 EUR 103.52 EUR	1.13 EUR 1.13 EUR	7.26 EUR 7.26 EUR	80.21 EUR 80.21 EUR	13.68 EUR 13.68 EUR
Standard	PAL
Device type	Digital timer
Sensor	1/3 " Sony EXMOR CMOS
Maximal current	16 A
Transparent door	—	...
Maximal load	3680 W
Matrix size	1.3 Mpx
Material	• Toggle Plug, Nylon • Screw, Steel galvanized
Resolution	1000 TVL
Measuring accuracy	≤ 1 minute / month
Drilling diameter	10 mm
Lens	2.8 mm
Expansion plug length	40 mm
Mounting standard	...	VESA : 200, 300, 400 x 200, 400, 600 x 400	...	VESA : 100, 200, 200x100
Material	Steel	...
Screw dimensions	Ø 5 x 60 mm
Screen size range	...	37 " ... 70 "	...	23 " ... 43 "
Timing range	1 minute ... 168 hours (7 days)
Bearing capacity	...	45 kg	...	30 kg
View angle	• 81 ° (manufacturer data) • 90 ° (our tests result)
Mounting panel thickness	9.5 ... 55 mm
Safety class	Grade 2	...
Range of IR illumination	20 m
The maximum countdown time	99 hours 59 minutes
Cavity depth	min. 40 mm
Distance from mounting surface	...	54 ... 448 mm	...	56 ... 204 mm
Compliance with standards	IEC 60695-2-1	...
Video output	1 Vpp 75 Ω
Tilt adjustment	...	-15 ° ... 15 °	...	-8 ° ... 5 °
Horizontal rotation	...	-60 ° ... 60 °	...	-90 ° ... 90 °
Rotation in the plane of the screen	...	± 3 °	...	—
Application	• plasterboard • Gypsum fibreboard • OSB board • MDF board • Concrete • Solid clay brick • Solid sand-lime brick	...	Distribution cabinets 4 x 24-modular - XL ³ S 160	...
Main features	• Reversible door • 1 closing point • Supplied with handle in the kit	• Time settings for switching electrical devices on and off • 16 programs • Manual or random on / off • 16 weekday combinations • Daylight saving (summer) and winter time function • 12 or 24 hour mode • Count down function • Large, readable LCD display • built-in battery
Security class	IP20
Socket type	2P+Z, E type

Main features	<ul style="list-style-type: none"> • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • Privacy zones - max. 8 • Motion Detection - max. 4 zones • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto)
OSD menu	✓
Vandal-proof	✓
Power supply	12 V / 270 mA	<ul style="list-style-type: none"> • 230 V AC, 50 Hz • built-in battery
Housing	Dome - Metal	Plastic
Color	Black	Silver / Black	...	Black	White	...
"Index of Protection"	IP65
Operation voltage	175 ... 276 V AC, 45 ... 65 Hz
Operation temp	-10 °C ... 45 °C	0 °C ... 50 °C
Weight	0.37 kg	4.76 kg	...	1.03 kg	4.9 kg	0.15 kg
Dimensions	Ø 94 x 70 mm	720 x 435 x (54 ... 448) mm	...	230 x 230 x (56 ... 205) mm	547 x 694 x 28 mm	115 x 55 x 78 mm
Manufacturer / Brand	Fischer	BRATECK	LEGRAND	ORNO
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years