



	<a href="#">ROUTER GPON CPE UF-WIFI UFiber Wi-Fi 2.4 GHz 300 Mbps UBIQUITI</a>	<a href="#">IP CAMERA DS-2CD1T67G2H-LIU(2.8MM)PL ColorVu - 6 Mpx Hikvision</a>
		
	39141.35 HUF 39141.35 HUF	90288.46 HUF 90288.46 HUF
Standard	...	IP
Frequency range	2.4 GHz	...
Antenna type	Omnidirectional antenna - embedded	...
Standards	IEEE 802.11n, ITU-G.984	...
Baud rates	300 Mbps	...
LAN ports	4 x 10/100/1000 Mbps	...
Resolution	...	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Sensor	...	1/2.4 " Progressive Scan CMOS
WAN interface	1 x port GPON SC/APC, 2.488 Gb/s Downlink / 1.244 Gb/s Uplink	...
Lens	...	2.8 mm
View angle	...	115 °
White light LED illuminator range	...	50 m
Range of IR illumination	...	50 m
Memory card slot	...	—
Optical power	• Tx : 1.5 ... 5 dBm • Rx : -28 ... -8 dBm	...
LED indicators	Power, LAN, Signal indicator	...
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Management interface	Ubiquiti Network Management System	...
Alarm inputs / outputs	...	—
Power supply PoE	Ubiquiti Passive PoE	...
Audio	...	• Microphone built-in, • Audio transmission via network
Main stream frame rate	...	20 fps @ 6 Mpx
Interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓

Main features	<ul style="list-style-type: none"> <li>• GPON - Gigabit Passive Optical Network - links support : 20 km (max)</li> <li>• VLAN support</li> <li>• Layer 2/3 advanced management features</li> <li>• "Dying gasp" function - message sent by the customer premises equipment to equipment managed by the ISP to indicate that the CPE device has lost power</li> <li>• RESET button</li> <li>• Possibility to mount to the wall</li> </ul>	...
Certificates	CE, FCC, IC	...
Main features	...	<ul style="list-style-type: none"> <li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Horizontal mirror image</li> <li>• Smart motion detection (with recognizing people and vehicles)</li> <li>• Configurable Privacy Zones</li> <li>• Sharpness - sharper image outlines</li> <li>• video tampering</li> <li>• Filtering of false alarms based on the recognition of persons and vehicles</li> </ul>
Operation temp	-10 °C ... 45 °C	...
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">Hik-Connect</a></li> <li>• iOS: Free application <a href="#">Hik-Connect</a></li> </ul>
Default IP address	192.168.1.1	192.168.1.64
Permissible relative humidity	10 % ... 90 %	...
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports	...	8000
Port ONVIF	...	80

RTSP URL	...	<ul style="list-style-type: none"> <li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li> <li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li> </ul>
Power supply	<ul style="list-style-type: none"> <li>• 20 V ... 28 V DC - 24 V DC / 0.5 A (power adapter included)</li> <li>• Passive PoE 24 V - Port 1 ("+": 4, 5 pins; "-": 7, 8 pins)</li> </ul>	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 600 mA</li> </ul>
Power consumption	≤ 7 W	<ul style="list-style-type: none"> <li>• ≤ 8.7 W @ PoE</li> <li>• ≤ 7.2 W @ 12 V DC</li> </ul>
Housing	...	Compact, Metal
Color	...	White
"Index of Protection"	...	IP67
Mechanical protection class	...	—
Operation temp	...	-30 °C ... 60 °C
Weight	0.19 kg	0.42 kg
Dimensions	126 x 126 x 32 mm	202 x 84 x 81 mm
Supported languages	...	Polish
Manufacturer / Brand	UBIQUITI	Hikvision
SAP Code	...	311327371
Guarantee	2 years	3 years

