




	CABLE 2C-W/2C-G-3.0M 3 m	VIDEO SEPARATOR D-SEP/HD-4	INSULATING TAPE TESAFLEX-7000V/20X19/BL TESA
			
	1.10 EUR 1.10 EUR	20.43 EUR 20.43 EUR	1.76 EUR 1.76 EUR
Length	20 m
Thickness	0.15 mm
Width	19 mm
Color	Blue
Material	PVC
Cable	2 x CINCH Plug / 2 x CINCH Socket
Length of the cable	3 m
Standard	...	<ul style="list-style-type: none"> • AHD - 8 Mpx, 4K UHD • HD-CVI - 8 Mpx, 4K UHD • HD-TVI - 8 Mpx 4K UHD • CVBS - PAL / NTSC 	...
Device type	...	Passive	...
Number of inputs	...	4 pcs BNC socket	...
Number of outputs	...	4 pcs BNC socket	...
Input impedance	...	75 Ω	...
Output impedance	...	75 Ω	...
Opto-isolation between inputs and outputs	...	50 V DC	...
Main features	<ul style="list-style-type: none"> • Very easy and quick assembly 	...	<ul style="list-style-type: none"> • Dielectric breakdown voltage : 7000 V, • Heat-resistant up to : 90 °C • Elongation at break : 240 % • Tensile strength : 25 N/cm • Adhesion to steel : 2.5 N/cm • Compliance with IEC 60454-3-1 (VDE, IMQ, SEMKO), VOC, RoHS 2.0, REACH
Galvanic separation between individual channels	...	> 2000 V	...
Attenuation	...	<ul style="list-style-type: none"> • 4.43 MHz @ 0.37 dB • 11 MHz @ 0.47 dB • 21 MHz @ 0.62 dB • 38 MHz @ 0.93 dB • 42 MHz @ 0.93 dB • 67.5 MHz @ 1.16 dB 	...

Bandwidth	...	200 MHz	...
Inputs protection	...	ESD, IEC 61000-4-2, $\pm 30\text{kV}$ contact, $\pm 30\text{kV}$ air EFT, IEC 61000-4-4, 40A (5/50ns) Lightning, IEC 61000-4-5, 30A ($t_p=8/20\mu\text{s}$)	...
Power supply	...	—	...
Operation temp	...	-20 °C ... 55 °C	...
Weight	0.073 kg	0.12 kg	...
Dimensions	...	103 x 78 x 30 mm	...
Manufacturer / Brand	...	DELTA	TESA
Guarantee	2 years	3 years	2 years