




	<a href="#">POWER DISTRIBUTION UNIT PR-1.5M-4G/B (4 OUTLETS) 1.3 m</a>	<a href="#">ELECTRIC CABLE YDY-5X2.5</a>	<a href="#">OVERVOLTAGE LIMITER AXON-POWER/DIN</a>
			
	3.71 EUR 3.71 EUR	2.60 EUR 2.60 EUR	35.62 EUR 35.62 EUR
Maximal voltage	...	...	250 V AC / 50 Hz
In section	...	<b>100 m . Price for 1m when buying a whole roll</b>	...
Total maximal current	10 A	...	...
Rated current	...	...	10 A
Maximal total load	2500 W	...	...
Protection level Up L/PE, N/PE	...	...	≤ 1.3 kV
Number of outlets	4 grounded outlets 10A/250V CEE 7/5	...	...
Protection level Up L/N	...	...	≤ 3 kV
Inner conductor	...	5 x 2.5 mm <sup>2</sup> - Cu wire	...
Fuse	—	...	...
Rated voltage	220 ... 240 V AC / 50 Hz	450 / 750 V	230 V AC / 50 Hz
Switch	—	...	...
Nominal discharge current (L/N, L/PE, N/PE)	...	...	4 kA - 8/20 μs
Wire gauge	3 x 1.5 mm <sup>2</sup>	...	...
Length of the cable	1.3 m	...	...
Outer coating	...	Ø 12 mm - PVC	...
Maximum stroke current (L/N, L/PE, N/PE)	...	...	10 kA 8/20 μs (type 2)
Coating color	...	White	...
Color	Black	...	...
Operation state indication	...	...	✓
Connectors type	...	...	2 x terminals
Housing	Plastic	...	• Plastic • DIN, TS-35 rail mounting
Weight	0.26 kg	...	0.075 kg
Dimensions	196 x 54 x 39 mm	...	86 x 58 x 35 mm
Guarantee	2 years	2 years	2 years