



|                       | <a href="#">ACCESS CONTROL PANEL<br/>ACCO-NT2 SATEL</a>   | <a href="#">POWER DISTRIBUTION<br/>UNIT LE-049494 (6<br/>OUTLETS) 3 m LEGRAND</a>  |
|-----------------------|---|--|
|                       |    |  |
|                       | 377.94 EUR<br>377.94 EUR  | 22.81 EUR<br>22.81 EUR   |
| Rated voltage         | ...   | 230 V AC / 50 Hz   |
| Total maximal current | ...   | 16 A   |
| Maximal total load    | ...   | 3680 W   |
| Inputs                | <ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 264</li> </ul>  | ...  |
| Number of outlets     | ...   | 6 grounded outlets<br>16A/250V CEE 7/5   |
| Fuse                  | ...   | —  |
| Switch                | ...   | —  |
| Outputs               | <ul style="list-style-type: none"> <li>• 8 pcs - Mainboard inputs</li> <li>• max. 264</li> </ul>  | ...  |
| Wire gauge            | ...   | 3 x 1.5 mm <sup>2</sup>  |
| Length of the cable   | ...   | 3 m  |
| Housing               | ...   | Plastic  |
| Communication         | <ul style="list-style-type: none"> <li>• 2 x RS-485</li> <li>• Expander bus - up to 32 expander modules</li> </ul>  | ...  |
| Color                 | ...   | White / Gray   |
| Events memory         | <ul style="list-style-type: none"> <li>• Events saving to the micro SD card (included)</li> <li>• Recording up to 1 000 000 events from the control panel,</li> <li>• Max. 100 000 events read from each access control module</li> </ul> | ...  |
| Users + admins        | <ul style="list-style-type: none"> <li>• 8000 + 1</li> <li>• Max. 65 000 users in the whole ACCO NET system</li> </ul>  | ...  |
| Output load           | <ul style="list-style-type: none"> <li>• OC : 50 mA / 12 V DC</li> <li>• +EX : 0.5 A / 12 V DC</li> <li>• AUX : 0.5 A / 12 V DC</li> </ul>  | ...  |

|                               |   |                  |
|-------------------------------|---|------------------|
| Main features                 | <ul style="list-style-type: none"> <li>• Support for up to 255 access control modules</li> <li>• Ability to create up to 255 partitions in 1 control panel (up to 255 access control modules can be defined in one partition)</li> <li>• Ability to add up to 16 passageways (up to 16 partitions can be defined in each passageway)</li> <li>• Ability to block/unblock partition at a specified time, or as per access schedule,</li> <li>• Ability to assign 4 identifiers and a keyfob to a single user,</li> <li>• Ability to assign up to 4 proximity cards / DALLAS chips (iButtons) to a user,</li> <li>• Up to 256 access calendars, weekly schedules, daily schedules, time frames</li> <li>• Ability to control the control panel outputs by using keyfobs</li> <li>• Implementation of logic functions on inputs and outputs</li> <li>• Support for turnstiles</li> <li>• Electrical protection of all inputs and outputs as well as communication buses</li> </ul> | ...              |
| Power supply                  | 12 V DC / 140 mA (max)  | ...              |
| Battery backup support        | —   | ...              |
| Operation temp                | -10 °C ... 55 °C  | ...              |
| Permissible relative humidity | 93 % (non-condensing)   | ...              |
| Weight                        | 0.096 kg  | 0.61 kg          |
| Dimensions                    | 151 x 69 x 17 mm  | 295 x 54 x 37 mm |
| Manufacturer / Brand          | SATEL   | LEGRAND          |
| Guarantee                     | 2 years   | 2 years          |