



	<a href="#">IP CAMERA APTI-AI508V3IW-36AD</a> Smart Dual Illumination Active Deterrence - 5 Mpx 2.8 mm	<a href="#">EXPANSION PLUG</a> KW-6/3.5X35 KLIMAS
		
	82.82 EUR 82.82 EUR	0.06 EUR 0.06 EUR
Standard	IP	...
Material	...	<ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> </ul>
Drilling diameter	...	6 mm
Expansion plug length	...	30 mm
Screw dimensions	...	Ø 3.5 x 35 mm, PZ-2
Application	...	<ul style="list-style-type: none"> <li>• Concrete</li> <li>• Solid clay brick</li> <li>• Solid sand-lime brick</li> </ul>
Resolution	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 720p	...
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS	...
Lens	2.8 mm @ F1.6	...
View angle	106 °	...
Range of IR illumination	25 m	...
White light LED illuminator range	25 m	...
Memory card slot	Micro SD memory cards up to 1TB support (possible local recording)	...
Image compression method	H.265+ / H.265 / H.264+ / H.264 / AVI / JPEG	...
Alarm inputs / outputs	1 / 1	...
Audio	<ul style="list-style-type: none"> <li>• Microphone built-in,</li> <li>• Speaker built-in,</li> <li>• Bi-directional audio streaming support</li> </ul>	...
Main stream frame rate	max. 25 fps @ 5 Mpx	...
Interface	10/100 Base-T (RJ-45)	...
WEB Server	Built-in	...
Max. number of on-line users	10	...
ONVIF	19.12	...

Intelligent image analysis	<ul style="list-style-type: none"> <li>• intrusion - classification of people and vehicles</li> <li>• crossing the line (tripwire) - classification of people and vehicles</li> <li>• detection of people gathering (human silhouette)</li> <li>• loitering detection (human silhouette)</li> <li>• motion detection based on human detection</li> </ul>	...
Main features	<ul style="list-style-type: none"> <li>• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li> <li>• Active deterrence function - Red and blue LEDs, Beep signal</li> <li>• Day/Night mode - configurable</li> <li>• ICR - Movable InfraRed filter</li> <li>• Configurable: brightness, contrast, saturation</li> <li>• Sharpness - sharper image outlines</li> <li>• Mirror - Mirror image</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• WB - White Balance</li> <li>• Flicker Control - The technology eliminates the tiring eyes flickering image effect</li> <li>• video tampering</li> <li>• HLC - High Light Compensation (spot)</li> <li>• Corridor mode</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• BLC - Back Light Compensation</li> <li>• WDR - Wide Dynamic Range</li> <li>• Motion Detection</li> <li>• Privacy zones - max. 3</li> <li>• AGC - Automatic Gain Control</li> </ul>	...
Mobile phones support	<p>Port no.: 80 or access by a cloud (P2P)</p> <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">BitVision</a></li> <li>• iOS (iPhone): Free application <a href="#">BitVision</a></li> </ul>	...
Default IP address	192.168.1.168	...
Default admin user / password	admin / admin	...
Web browser access ports	80	...
PC client access ports	80	...
Mobile client access ports	80	...
Port ONVIF	80	...

RTSP URL	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream	...
Power supply	• PoE (802.3af), • 12 V DC / 350 mA	...
Power consumption	≤ 4.2 W	...
Housing	Dome, Metal	...
Color	White	...
"Index of Protection"	IP67	...
Mechanical protection class	—	...
Operation temp	-30 °C ... 60 °C	...
Weight	0.73 kg	...
Dimensions	Ø 127 x 120 mm	...
Supported languages	Polish, English, French, Russian, Hebrew, Spanish, Portuguese, Italian, Ukrainian, Hungarian	...
Manufacturer / Brand	APTI	KLIMAS
Guarantee	2 years	2 years