






	THERMOSTAT FZK-011	WEATHER STATION UT-A13T UNI-T	CABLE PAIR DETECTOR WITH RJ-45 CABLE TESTER UT-682 UNI-T	RJ-45 PLUG INTERNAL SHIELD RJ45/WP-G/IN	EXTENDER HDMI-EX-120-4K-V4
					
	27.64 CAD 27.64 CAD	20.48 CAD 20.48 CAD	44.29 CAD 44.29 CAD	0.05 CAD 0.05 CAD	264.92 CAD 264.92 CAD
Supported HDMI standard	1.4
Application	RJ-45 modular plug internal shield	...
Sensor type	Bimetallic
HDCP	1.4
Measurement	...	Temperature / relative humidity
Material	Plastic	...
Protocols	HDBiT
Tested cables	UTP, FTP, YTKSY - RJ45 (8P8C), RJ11 (6P4C)
Measurement range	...	-10 °C ... 50 °C ± 1 °C
Contact type	<ul style="list-style-type: none"> • 1 x NC - opened after exceeding the set temperature, • 1 x NO - closed after exceeding the set temperature
Maximal power voltage	250 V AC
Measurement of humidity	...	20 % ... 95 % ± 5 %
Relay maximal load	<ul style="list-style-type: none"> • 10 A - NC, • 5 A - NO
Temperature set range	-20 °C ... 60 °C
Hysteresis	7 °C ± 4 °C
Supported HDMI resolutions	<ul style="list-style-type: none"> • 480i @ 60Hz, • 480p @ 60Hz, • 576i @ 50Hz, • 576p @ 50Hz, • 720p @ 50/60Hz, • 1080i @ 50/60Hz, • 1080p @ 50/60Hz, • 4K UHD @ 24/25/30Hz
Color	...	White	...	Green	...
"Index of Protection"	IP20
Assembly	DIN TS-35 rail
Permissible relative humidity	...	max. 90 % (non-condensing)	20 % ... 75 %
Maximal transmission range	<ul style="list-style-type: none"> • 80 m UTP cat. 5 • 100 m UTP cat. 5e • 120 m UTP cat. 6
Weight	0.062 kg	0.106 kg	<ul style="list-style-type: none"> • 0.11 kg - Transmitter • 0.14 kg - Receiver 	0.0005 kg	...
Main features	...	<ul style="list-style-type: none"> • LCD display • Digital sensor • Alarm function • Calendar function • Selectable measurement unit: °C / °F • Wall mounting • Integrated stand 	<ul style="list-style-type: none"> • Test for the presence of a short circuit, open circuit • Polarity indicator for telephone wire pairs : ± (5V ... 52V) • The maximum length of the telephone line : 3000 m • Optical - sound signaling • Low battery indicator 	...	<ul style="list-style-type: none"> • IR carrier frequency : 20 kHz ... 60 kHz • Protections : lightning, Overvoltage, ESD
Manufacturer / Brand	...	UNI-T	UNI-T
Power supply	...	1 x battery LR3 (AAA) (included)	2 x 9V, type 6F22 battery (included)	...	5 V DC / 2 A (2 pcs of power supply adapters included)
Current consumption	<ul style="list-style-type: none"> • 4 W Receiver • 6 W Transmitter

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Operation temp	-20 °C ... 80 °C	-10 °C ... 50 °C	0 °C ... 40 °C	...	0 °C ... 60 °C
Transmitter and receiver weight	0.33 kg
Dimensions	65 x 50 x 38 mm	Ø 130 x 78 mm x 22 mm	• 125 x 48 x 29 mm - Transmitter • 194 x 50 x 30 - Receiver	20.3 x 11.7 x 7.9 mm	113 x 95 x 24 mm
Guarantee	2 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00