



	TV OR MONITOR MOUNT BRATECK-LPA68-223	IP CAMERA DS-2CD1043G2-I(2.8MM) - 3.7 Mpx Hikvision
		
	6.55 EUR 6.55 EUR	156.25 EUR 156.25 EUR
Standard	...	TCP/IP
Sensor	...	1/3 " Progressive Scan CMOS
Mounting standard	VESA 100, 200	...
Matrix size	...	4 Mpx
Screen size range	23 " ... 43 "	...
Bearing capacity	30 kg	...
Distance from mounting surface	56 ... 378 mm	...
Tilt adjustment	-10 ° ... 3 °	...
Resolution	...	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens	...	2.8 mm
Horizontal rotation	-90 ° ... 90 °	...
Rotation in the plane of the screen	—	...
View angle	...	• 99 ° (manufacturer data) • 95 ° (our tests result)
Range of IR illumination	...	30 m
Memory card slot	...	—
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	—
Main stream frame rate	...	• 20 fps @ 3.7 Mpx • 25 fps @ 1080p
Network interface	...	10/100 Base-T (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	6
ONVIF	...	✓
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) • Android: Free application Hik-Connect • iOS: Free application Hik-Connect
Default admin user / password	...	admin / -
Default IP address	...	192.168.1.64
Web browser access ports	...	80
PC client access ports	...	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mobile client access ports	...	8000
Port ONVIF	...	80
RTSP URL	...	<ul style="list-style-type: none"> • Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/ - with authorization • Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ - with authorization
Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Day/night mode • Mirror - Mirror image • Configurable Privacy Zones • Smart motion detection (with recognizing people and vehicles) • Sharpness - sharper image outlines
Power supply	...	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 410 mA
Power consumption	...	<ul style="list-style-type: none"> • ≤ 5 W @ 12 V DC • ≤ 6.5 W @ PoE (802.3af)
Housing	...	Compact - Metal + Plastic
Color	Black	White
"Index of Protection"	...	IP67
Operation temp	...	-30 °C ... 60 °C
Weight	1.7 kg	0.27 kg
Dimensions	230 x 230 x (56 ... 378) mm	171 x 70 x 66 mm
Supported languages	...	Polish, English, Croatian, Czech, Romanian, Serbian, Slovenian, Slovak, Turkish, Ukrainian
Manufacturer / Brand	BRATECK	Hikvision
SAP Code	...	311320661
Guarantee	2 years	3 years

