



	SMART GATE AND DOOR CONTROLLER SBW-02/ANT Wi-Fi, 12 ... 24 V AC/DC ZAMEL	PHOTOCELL FAAC-XP20D TXRX SET
		
	72.07 CHF 72.07 CHF	74.57 CHF 74.57 CHF
Support	SUPLA	...
Application	swing gates, sliding gates, garage gates, doors	...
Rated voltage	12 ... 24 V AC/DC	...
Beam width	...	$\pm 7^\circ @ 20 \text{ m}$, $\pm 13.5^\circ @ 5 \text{ m}$
Total maximal current	3 A @ 24 V AC	...
Operation range	...	20 m
Number of inputs	2	...
Number of outputs	2	...
Response time	...	13 ms
Connector type	screw terminals	...
Power supply	...	24 V AC/DC
Current consumption	...	• 20 mA Transmitter • 30 mA Receiver
Wireless	Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n	...
Number of relay outputs	...	1
Mobile phones support	• The SUPLA free application on Android • The SUPLA free application on iOS	...
Relay maximal load	...	max. 60 VA / 24 W
Output	...	1 x NC
Main features	<ul style="list-style-type: none"> • Control from a Web browser, • Local control by physical button, • schedule, • timer, • remote access, • voice control, • Possibility to manually program scenarios from the built-in API, • SMA RP connector for an external antenna 	<ul style="list-style-type: none"> • Cooperation with the FAAC gate automation system • Angle adjustment range $\pm 90^\circ$ horizontal • Surface/column mounting • Immunity to environmental changes
Housing	Plastic	Plastic
"Index of Protection"	IP20	IP54

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Color	Green	Black
Operation temp	-20 °C ... 55 °C	-20 °C ... 55 °C
Weight	0.039 kg	<ul style="list-style-type: none"> • 0.070 kg Transmitter • 0.076 Receiver
Dimensions	57 x 47 x 20 mm	130 x 42 x 41 mm Transmitter / Receiver
Manufacturer / Brand	ZAMEL	FAAC
Guarantee	2 years	2 years