

	TV OR MONITOR MOUNT AX-MAGNUM	ACCESS CONTROLLER PR102DR	EXPANSION PLUG KW-6/3.5X50 KLIMAS	MEASURING CONNECTOR 2-PIN LSA-W	KRONE BACK-MOUNT FRAME LSA-GN-10/10	SMART SWITCH SWITCHBOX-LIGHT/BLEBOX Wi-Fi, 230 V AC
						
	186.18 NOK 186.18 NOK	1029.62 NOK 1029.62 NOK	0.82 NOK 0.82 NOK	7.33 NOK 7.33 NOK	88.01 NOK 88.01 NOK	291.26 NOK 291.26 NOK
Number of pins	...	...	...	2 pcs	...	...
Number of mounted profile modules	...	...	...	...	10 pcs	...
Environment class	...	I	...	...	...	...
Mounting standard	VESA max. 600 x 400	...	...	...	...	...
Rated voltage	...	...	...	...	...	230 V AC
Type of mounted profile modules	...	...	...	...	10PAR	...
Relay contacts load	...	1.5 A / 30 V	...	...	...	...
Screen size range	32 " ... 65 "	...	...	...	...	...
Material	...	...	Expansion plug, Polypropylene Screw, Steel galvanized	...	...	...
Maximal total load	...	...	...	...	...	1150 W / 1150 VA
Battery backup support	...	—	...	...	...	...
Bearing capacity	30 kg	...	...	...	...	...
Drilling diameter	...	...	6 mm	...	...	...
Total maximal current	...	...	...	...	...	5 A
Input lines	...	2	...	...	...	...
Distance from mounting surface	58 mm	...	...	...	...	...
Expansion plug length	...	...	30 mm	...	...	...
Number of inputs	...	...	...	...	...	1
Output lines	...	2	...	...	...	...
Number of outputs	...	...	...	...	...	1
Communication	...	RS-485 RACS (Roger)	...	...	...	...
Connector type	...	...	...	...	...	screw terminals
Tilt adjustment	-15 ° ... 5 °	...	...	...	...	...
Screw dimensions	...	...	Ø 3.5 x 50 mm, PZ-2	...	...	...
Power supply	...	10 ... 15 V DC	...	...	...	...
Horizontal rotation	—	...	...	...	...	...
Rotation in the plane of the screen	—	...	...	...	...	...
Wireless	...	...	...	...	...	Wi-Fi, 2.4 GHz - IEEE 802.11g
Application	...	...	Concrete Solid clay brick Solid sand-lime brick	...	...	switching devices on/off
Mobile phones support	...	...	...	...	...	The <a href="#">wBox</a> free application on Android The <a href="#">wBox</a> free application on iOS
Permissible relative humidity	...	10 ... 95 % (non-condensing)	...	...	...	...
Main features	In the kit : Expansion plugs Ø 8 x 50 mm	PRT series readers support DIN, TS-35 rail mounting 4000 indexed users History of 32000 events Real-time clock and calendar Remote programming from PC	...	...	...	Local control by physical button, schedule, timer, remote access, voice control, The ability to set the default status of the device after a power failure, µWiFi technology support
Housing	...	...	...	...	...	Plastic
"Index of Protection"	...	...	...	...	...	IP20
Color	Black	...	...	...	...	Black
Operation temp	...	5 °C ... 40 °C	...	...	...	-20 °C ... 50 °C
Weight	1.27 kg	0.13 kg	...	0.003 kg	...	0.027 kg
Dimensions	640 x 420 x 50 mm	98 x 88 x 73 mm	...	49 x 14 x 9.5 mm	225 x 112 x 50 mm	38 x 25 x 23 mm
Manufacturer / Brand	...	ROGER	KLIMAS	...	...	BleBox
Guarantee	2 years	2 years	2 years	...	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00