




	ACCESS POINT RB-D52G-5HACD2HND-TC-HAP-AC2 hAP ac², 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps MIKROTIK	NVR DS-7732NXI-I4/S(E) 32 CHANNELS ACUSENSE Hikvision	FRAME PLATE LE-665005 Niloe LEGRAND
			
	74.27 GBP 74.27 GBP	1072.59 GBP 1072.59 GBP	4.18 GBP 4.18 GBP
Standard	...	TCP/IP	...
Application	Niloe product series
Number of sections	5
Frequency range	2.4 GHz, 5 GHz
Supported resolutions	...	max. 32 Mpx	...
Material	Self-extinguishing ABS
Antenna type	4 x Internal antenna
Color	White (RAL 9003)
"Index of Protection"	IP44
IK rating	IK04
Standards	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Video outputs	...	2 pcs HDMI 4K 1 pcs VGA 1 pcs CVBS There is a possibility to configure a SPOT function on one of the output	...
Baud rates	300 Mbps + 867 Mbps
Audio support	...	<ul style="list-style-type: none"> • 32 Channels - Audio from cameras • Bi-directional audio streaming support 	...
Audio inputs	...	1 pcs CINCH	...
LAN ports	4 x 10 / 100 / 1000 Mbps LAN 1 x 10 / 100 / 1000 Mbps Uplink
Audio outputs	...	1 pcs CINCH	...
LED indicators	Power, User, 4 x Ethernet, WAN, WPS
Image compression method	...	H.265+ / H.265 / H.264+ / H.264	...
Bitrate	...	max. 256 Mbps	...
Supported hard drives	...	4 x 10 TB SATA + 1 x eSATA	...
Recording modes	...	Manual, Sensor, Motion detection, Schedule	...
External storage devices backup	...	Backup to USB drive (pendrive, external drive)	...
Searching and playback the records	...	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Records playback from max. 16 channels in the same time @ 1080p	...
Network interface	...	2 x RJ-45 10/100/1000 Base-TX	...
Network functions	...	<ul style="list-style-type: none"> • Live image view, Playback the records, Backup the records • max. 128 on-line users - iVMS-4200 application 	...
Receiver sensitivity	2.4 GHz : <ul style="list-style-type: none"> • 1M : -100 dBm • 11M : -94 dBm • 6M : -96 dBm • 54M : -78 dBm • MCS0 : -96 • MCS7 : -73 5 GHz : <ul style="list-style-type: none"> • 6M : -96 dBm • 54M : -80 dBm • MCS0 : -96 dBm • MCS7 : -75 dBm • MCS9 : -70 dBm

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

DDNS	✓
DHCP server	✓
Firmware update	✓
Management interface	Web browser
Network protocols	...	TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS	...
ONVIF	...	✓	...
Default IP address	...	192.168.1.64	...
Transmitter power	max. 27 dBm @ 2.4 GHz max. 26 dBm @ 5 GHz
Default admin user / password	...	admin / - The administrator password should be set at the first start	...
Mobile phones support	...	Port no.: 8000 or access by a cloud (P2P) Android: Free application Hik-Connect iOS: Free application Hik-Connect	...
Web browser access ports	...	80, 8000	...
PC client access ports	...	8000	...
Mobile client access ports	...	8000	...
Main features	<ul style="list-style-type: none"> • Built-in 4-port switch • The WPS function allows to easy establish an encrypted connection • WMM (Wi-Fi Multimedia) • Port USB • IPsec • Mode button
RTSP URL	...	<ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream 	...
USB	...	2 pcs USB 2.0 1 pcs USB 3.0	...
Serial ports	...	2 pcs RS-485 1 pcs RS-232	...
Alarm inputs / outputs	...	16 / 9	...
PTZ control	...	<ul style="list-style-type: none"> • IP Speed Dome Cameras • RS-485 - PELCO-D/P and others 	...
Motion Detection	...	2.0	...
Intelligent image analysis	...	✓	...
Main features	...	<ul style="list-style-type: none"> • NVR from the AcuSense series • Intelligent image analysis : crossing the line (tripwire), intrusion, Face recognition, Motion detection with human/vehicle silhouette recognition • Filtering of false alarms based on the recognition of persons and vehicles • Comparison of faces with images from the database • supports 4 types of facial attributes extraction • Support for up to 16 face databases, including 50 000 face images • Smart search for a person based on a face photo • Cooperation with POS (Point of Sale) terminals • Power outputs : 12 V DC / 1 A, 12 V DC / 0.5 A (controlling) <p>Functions implemented in cooperation between the recorder and cameras that support these functions :</p> <ul style="list-style-type: none"> • ANPR • people counting 	...



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Mouse support	...	✓	...
IR remote controller in the set	...	—	...
Power supply	<ul style="list-style-type: none"> • 12 ... 30 V DC / 0.8 A (power adapter included) • 18 ... 28 V DC - Passive PoE 	100 ... 240 V AC / 50 ... 60 Hz	...
Power consumption	...	max. 30 W (without HDD)	...
Operation temp	-40 °C ... 50 °C	-10 °C ... 55 °C	-5 °C ... 35 °C
Weight	0.17 kg	4.1 kg	0.040 kg
Dimensions	120 x 99 x 33 mm	445 x 402 x 75 mm, RACK 19", 1.5U	50.6 x 50.6 mm (total size of the hole) 71 mm (distance between holes centers) 370 x 86 x 10 mm
Supported languages	...	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian	...
Manufacturer / Brand	MikroTik	Hikvision	LEGRAND
SAP Code	...	303618605	...
Guarantee	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00