

	<a href="#">UPS COVER-WINTER-3K 3000 VA COVER</a>	<a href="#">EXTENDER EXT-POE3H IN A HERMETIC CASING PULSAR</a>	<a href="#">VIDEO SEPARATOR WITH OPTO-ISOLATION SV-1000A STANDARD: AHD, HD-CVI</a>	<a href="#">EXPANSION PLUG JKP-12X220/M5 EBOLT</a>
				
	497.24 EUR 497.24 EUR	67.68 EUR 67.68 EUR	38.02 EUR 38.02 EUR	1.99 EUR 1.99 EUR
Power adapter type	Line-interactive	...	...	...
Nominal power	2700 W	...	...	...
Apparent Power	3000 VA	...	...	...
Standards	...	PoE : 802.3af/at - Port PoE OUT 1/2, Passive PoE - Port PoE OUT 3	...	...
Input voltage	162 V ... 290 V AC	42 ... 57 V DC	...	...
Material	...	...	...	<ul style="list-style-type: none"> <li>• Expansion plug, Polypropylene</li> <li>• Screw, Steel galvanized</li> <li>• mounting screw, Steel galvanized</li> </ul>
Standard	...	...	<ul style="list-style-type: none"> <li>• AHD - 4 Mpx</li> <li>• HD-CVI - 720p</li> <li>• CVBS - PAL / NTSC</li> </ul>	...
Drilling diameter	...	...	...	12 mm
Input frequency	50 / 60 Hz	...	...	...
Expansion plug length	...	...	...	215 mm
Number of inputs	...	1	1 pcs BNC	...
Input impedance	...	...	75 Ω	...
Connector	...	4 x RJ-45 socket	...	...
Output impedance	...	...	75 Ω	...
Screw dimensions	...	...	...	Ø 8 x 220 mm, Internal thread M5
Galvanic (optical) isolation between signal inputs and outputs	...	...	1000 V peak	...
Output voltage	208 V / 220 V / 230 V / 240 V AC (Pure Sine Wave)	42 ... 57 V DC	...	...
LED indicators	...	LAN, PoE	...	...
Opto-isolation between power and signal inputs / outputs	...	...	1000 V peak	...
Power factor	0.9	...	...	...
Screw	...	...	...	Ø 5 x 16 mm
Application	...	...	...	for Styrofoam 150 mm
Gain adjustment	...	...	-3 dB ... +3 dB	...
Bandwidth	...	...	33 MHz / 1 Vpp	...
Output frequency	50 / 60 Hz (auto detection) ± 1 Hz	...	...	...
Transfer time	max. 6 ms	...	...	...
Power supply	...	...	12 V DC / 90 mA	...
Voltage adjustment	—	...	...	...

Frequency adjustment	—	...	...	...
Supported data rates	...	<ul style="list-style-type: none"> <li>• Range : 100 m - Input, 100 m - 3 x Output,</li> <li>• Supported data rates 10 / 100 Mbps - Fast Ethernet</li> </ul>	...	...
Charging time (recover to 90% capacity)	8 hours	...	...	...
Battery	6 pcs	...	...	...
Output power	...	19.2 W / Port PoE OUT 1/2 , 14.4 W / Port PoE OUT 3 , max. 19.2 W (total)	...	...
Estimated battery operation time	<ul style="list-style-type: none"> <li>• 12 minutes @ 1350 W,</li> <li>• 7 minutes @ 2025 W,</li> <li>• 4 minutes @ 2700 W</li> </ul>	...	...	...
Housing	...	Plastic, hermetic	...	...
"Index of Protection"	...	IP56	...	...
Number of outputs	8 pcs IEC-320 C13 + 1 pcs IEC-320 C19	3	1 pcs BNC	...
Management software	ViewPower	...	...	...
Protections	<ul style="list-style-type: none"> <li>• Short-circuit</li> <li>• Overload</li> <li>• Overcharge protection</li> <li>• discharge protection</li> <li>• Output voltage filtering</li> <li>• EPO (Emergency power off) switch</li> </ul>	<ul style="list-style-type: none"> <li>• Overvoltage</li> <li>• Overload</li> <li>• Short-circuit</li> </ul>	...	...
Operation state indication	<ul style="list-style-type: none"> <li>• LCD display: operation mode, battery charging level, in/out voltage level,</li> <li>• Sound signaling</li> </ul>	...	...	...
Main features	<ul style="list-style-type: none"> <li>• Auto restart while AC is recovering</li> <li>• Automatic bypass</li> <li>• The device has a rotating display</li> <li>• COLD START function for manual switch to the battery power supply</li> <li>• Battery charge and maintenance control</li> <li>• Port RS-232 - Access from PC</li> <li>• Remote management - ViewPower application (included)</li> <li>• Battery replacement during operation (Hot-swap)</li> <li>• Network card slot</li> <li>• Can be mounted in a Rack 19" cabinet</li> </ul>	...	...	...
Application	<ul style="list-style-type: none"> <li>• Surveillance Systems</li> <li>• data storage centers</li> <li>• network, servers, workstations</li> <li>• Industrial Equipment</li> </ul>	...	...	...
Housing type	Rack/Tower 2-in-1 Design	...	...	...

Operation temp. / Relative humidity	0 °C ... 40 °C / 0 ~ 95 % (non-condensing)	-25 ... 50 °C / 10 ... 90 %	...	...
Weight	29.2 kg	0.55 kg	0.088 kg	...
Dimensions	438 x 630 x 88 mm ; RACK 19", 2U	198 x 148 x 80 mm	120 x 62 x 30 mm	...
Manufacturer / Brand	COVER	PULSAR	DELTA	EBOLT
Guarantee	2 years	2 years	3 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00