

	ACCESS POINT 4G+ LTE Cat. 6 +ROUTER LTE-CA2-103 Wi-Fi 2.4 GHz, 5 GHz, 866 Mbps + 300 Mbps	ROUTER RG-EG105G-P-V2, 4 PoE REYEE	ACCESS POINT +ROUTER ARCHER-VR300 VDSL / ADSL 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps TP-LINK
			
	175.95 AUD 175.95 AUD	265.77 AUD 265.77 AUD	103.42 AUD 103.42 AUD
Frequency range	<ul style="list-style-type: none"> • Wi-Fi : 2.4 GHz, 5 GHz, • LTE : 2600 MHz, 2500 MHz, 2300 MHz, 2100 MHz, 1800 MHz, 900 MHz, 850 MHz, 800 MHz, 700 MHz 	...	2.4 GHz, 5 GHz
Port USB	...	—	...
Antenna type	<ul style="list-style-type: none"> • 4 x Omnidirectional antenna Wi-Fi, Integrated, • 2 x Omnidirectional antenna 4G LTE, Integrated 	...	4 x Omnidirectional antenna 5 dBi
Standards	IEEE 802.11 b/g/n/ac	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, 802.3z, IEEE 802.3af, IEEE 802.3at	IEEE 802.11 b/g/n, IEEE 802.11 a/n/ac, IEEE 802.3, IEEE 802.3u, IEEE 802.3ab ITU G.993.2, ITU-T G.993.5 (G.vector), ITU-T G.998.4 (G.INP), Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite), ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.992.3 (G.DMT.bis), ITU-T G.992.4 (G.lite.bis), ITU-T G.992.5
Power supply PoE	...	Power output - LAN ports : PoE (802.3af/at) max. 54 W (total)	...
Mobile phones support	...	Android: Free application Ruijie Rejee iOS (iPhone): Free application Ruijie Rejee	...
LAN ports	1 x 10/100/1000 Mbps - Uplink / LAN 4 x 10/100/1000 Mbps - LAN	<ul style="list-style-type: none"> • 3 x LAN & PoE 10/100/1000 Mbps (RJ-45) • 1 x LAN & PoE / WAN 10/100/1000 Mbps (RJ-45) 	<ul style="list-style-type: none"> • 1 x 10/100 Mbps - LAN/WAN, • 3 x 10/100 Mbps - LAN
WAN interface	...	<ul style="list-style-type: none"> • 1 x WAN x 10/100/1000 Mbps (RJ-45) 	<ul style="list-style-type: none"> • 1 x RJ-11, ADSL / ADSL2 / ADSL2+ / VDSL / VDSL2 • 1 x RJ-45

LED indicators	Power, SYS, LTE, Wi-Fi, 4 x Ethernet, WAN	Status, Link/Act	Power, DSL, INTERNET, WLAN, LAN
SIM socket	1 x mini SIM
Baud rates	<ul style="list-style-type: none"> • Wi-Fi : 866 Mbps + 300 Mbps, • LTE Cat. 6 : 300 Mbps / 50 Mbps 	...	300 Mbps @ 2.4 GHz + 867 Mbps @ 5 GHz
DHCP server	✓	✓	✓
Firmware update	✓	✓	✓
DDNS	✓	✓	<ul style="list-style-type: none"> • DynDNS • No-IP
Power consumption	...	max. 60 W (at full load)	...
Transmitter power	< 20 dBm	...	< 20 dBm @ 2.4 GHz , < 23 dBm @ 5 GHz
Operation modes	ADSL/VDSL modem, Router, Access Point, Bridge WDS
Protections	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	<ul style="list-style-type: none"> • ACL • IP-MAC Binding • MAC addresses filtering • Support for dynamic ARP mapping and static table • NAT / NAPT • Port Mapping 	<ul style="list-style-type: none"> • LAN : NAT, SPI network firewall, Access control, IP-MAC Binding, Support DoS defence, parental control • WLAN : WEP 64/128-bit, WPA/WPA2, WPA-PSK/WPA2-PSK, QSS (Quick Secure Setup) - WPS
Management interface	Web browser	<ul style="list-style-type: none"> • Ruijie Cloud Central Management System • Configuration using the Ruijie Reyee application • Remote management • Web browser 	Web browser, TP-LINK Tether

Main features	<ul style="list-style-type: none"> Built-in 5-port switch RESET button Remote management 	<ul style="list-style-type: none"> VPN networks: IPsec VPN, Open VPN, L2TP VPN, PPTP VPN, etc. Static / dynamic routing WAN : PPPoE, PPTP, L2TP DHCP client/server support Access Control List - ACL package filtering based on source and destination IP addresses Rate limit Load balance NAT View topology and network status RESET button 	<ul style="list-style-type: none"> Enable/disable wireless network SSID hiding QoS WMM (Wi-Fi Multimedia), Rate limit Internet access filtering Wireless transmission statistics Firewall Remote management DHCP : DHCP server, DHCP client list Port forwarding : Virtual Server, Port Triggering, DMZ, ALG, UPnP VPN networks: IPsec VPN, L2TP VPN, PPTP VPN, VPN Pass-through IPv6 compliance Static / dynamic routing Port Mapping IGMP Snooping V1/V2/V3 Guest Network - a separate and secure network for guests Built-in 4-port switch ON/OFF button WPS button The WPS function allows to easy establish an encrypted connection RESET button The DSL line splitter included
Power supply	12 V DC / 1 A (power adapter included)	54 V DC / 1.15 A (power adapter included)	12 V DC / 1 A (power adapter included)
Operation temp	...	0 °C ... 40 °C	0 °C ... 40 °C
Permissible relative humidity	...	10 % ... 90 % (non-condensing)	10 % ... 90 %
Weight	0.42 kg	0.43 kg	0.31 kg
Dimensions	238 x 149 x 33 mm	207 x 109 x 28 mm	257 x 160 x 37 mm
Manufacturer / Brand	...	RUIJIE / REYEE	TP-LINK
Guarantee	2 years	2 years	2 years