



	WIRELESS DOOR CHIME ATLO-DB-TUYA	IP CAMERA TC-C38XS SPEC:I3/E/Y/M/2.8MM/V4.0 - 8 Mpx 2.8 mm TIANDY
		
	9.43 AUD 9.43 AUD	472.28 AUD 472.28 AUD
Standard	...	IP
Signaling mode	Optical - sound signaling	...
Number of ring-tones	52	...
Volume adjustment	4 volume levels, 10 ... 90 dB	...
Operation range	80 m - in open area	...
Frequency band	433.92 MHz ± 0.2	...
Main features	<ul style="list-style-type: none"> • Low power consumption • Receiver sensitivity : -110 dBm • Simple and quick device installation 	...
Resolution	...	3840 x 2160 - 8 Mpx , 3072 x 2048 - 6 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor	...	1/2.8 " Progressive Scan CMOS
Lens	...	2.8 mm
View angle	...	105 °
Range of IR illumination	...	30 m
Memory card slot	...	Micro SD card support up to 512GB
Image compression method	...	S+265 / H.265 / H.264
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in • Audio detection • Compliance with the AAC standard
Main stream frame rate	...	<ul style="list-style-type: none"> • 20 fps @ 8 Mpx • 25 fps @ 3.7 Mpx
Interface	...	10/100 Base-TX (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	2
ONVIF	...	✓

Mobile phones support	...	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address	...	192.168.1.2
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	...	3000, 3001
PC client access ports	...	3000, 3001
Port ONVIF	...	80
Intelligent image analysis	...	<ul style="list-style-type: none"> • classification of people and vehicles • crossing the line (tripwire) • intrusion



Main features	...	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ROI - improve the quality of selected parts of image • Corridor mode • AGC - Automatic Gain Control • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Day/night mode • Motion Detection
Power supply	100 ... 240 V AC	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 670 mA
Power consumption	≤ 0.5 W	≤ 8.5 W
Housing	Plastic	Dome - Metal
Color	White	White
"Index of Protection"	...	IP66
Mechanical protection class	...	—
Operation temp	...	-40 °C ... 65 °C
Weight	0.06 kg	0.49 kg
Dimensions	82 x 82 x 65 mm	Ø 117 x 96 mm
Supported languages	...	Polish, English, Albanian, Arabic, Hebrew, Spanish, Dutch, Korean, French, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	...	TIANDY
Guarantee	2 years	3 years