



	POLE MOUNT BCS-ASM	ACCESS CONTROLLER WITH TEMPERATURE MEASUREMENT DS-K1TA70MI-T - 1080p Hikvision
		
	22.90 EUR 22.90 EUR	1807.07 EUR 1807.07 EUR
Suitable for cameras	BCS, DAHUA	...
Scanning system	...	Progressive
Pole diameters range	Ø 80 ... Ø 150 mm	...
Material	Aluminum	...
Resolution	...	1920 x 1080 - 1080p
Sensor	...	CMOS Uncooled VOx microbolometer
Matrix size	...	2.1 Mpx 120 x 160 px
Temperature measurement	...	✓
Temperature measurement range	...	30 °C ... 45 °C
Accuracy of temperature measurement	...	± 0.5 °C
Temperature measurement distance	...	0.3 ... 1.8 m
Cards support	...	13.56 MHz S50
Reading distance of prox-keys	...	~ 5 cm
Face recognition distance	...	0.3 m ... 1.8 m
Memory	...	Memory of 6000 face templates Memory of 6000 RFID cards Non-volatile log buffer of the last 100 000 events
Standard	...	TCP/IP
IR illuminator	...	✓
LED illuminator	...	✓
Video output	...	—
RS-485 interface	...	✓

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Memory card slot	...	—
Alarm inputs / outputs	...	2 / 1
Audio	...	Speaker built-in
Network interface	...	10/100/1000 Base-T (RJ-45)
Network protocols	...	TCP/IP
WEB Server	...	—
ONVIF	...	—
RS-485	...	✓
Default IP address	...	192.168.1.64
Default admin user / password	...	admin / - The administrator password should be set at the first start
PC client access ports	...	port 8000
Main features	...	<ul style="list-style-type: none"> • Detection of people without a mask - access denied or voice alerts • Temperature measurement • 7 " capacitive touch screen - 1024 x 600 px • Mechanical tamper protection • Wiegand 34/26 • AGC - Automatic Gain Control • Sharpness - sharper image outlines • Day/Night mode (color/b&w/auto) • AI detection : A solution dedicated to measuring temperature. The camera is able to detect increased object temperature
Power supply	...	12 V DC / 2 A (power adapter not included)
Power consumption	...	≤ 24 W
Housing	...	Compact - Metal
Color	White	Silver + Black
"Index of Protection"	...	—
Operation temp	...	0 °C ... 50 °C
Weight	...	1.34 kg
Dimensions	126 x 114 x 20 mm	117 x 290 x 35 mm (without bracket)

Supported languages	...	Polish, English, French, Spanish, Portuguese, Russian, Italian
Manufacturer / Brand	BCS	Hikvision
SAP Code	...	302917212
Guarantee	3 years	3 years