



	WIRELESS VIDEO DOORPHONE ATLO-DBC52-TUYA Wi-Fi, Tuya Smart	AHD, HD-CVI, HD-TVI CAMERA APTI-H51V2-28 2Mpx / 5Mpx 2.8 mm
		
	94.87 EUR 94.87 EUR	29.85 EUR 29.85 EUR
Standard	...	AHD, HD-CVI, HD-TVI
Sensor	SmartSens CMOS - 2 Mpx	1/3 " Progressive Scan CMOS
Matrix size	...	5 Mpx
IR illuminator	5 ... 10 m	...
LED illuminator	—	...
proximity reader built-in	Unique EM 125kHz	...
Wireless transmission range	The range limited only by the availability of the Wi-Fi network	...
Wi-Fi standard	2.4 GHz IEEE 802.11 b/g/n	...
Network interface	<ul style="list-style-type: none"> • 10/100 Mbps Fast Ethernet, RJ-45 socket • 2.4 GHz Wi-Fi 	...
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS	...
Image compression method	H.265 / H.264	...
Supported audio formats	G.711	...
Resolution	1920 x 1080 px - 1080p	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI @ 30 fps, 25 fps, 15 fps , 2560 x 1440 - 4 Mpx @ HD-CVI @ 30 fps, 25 fps , 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 30 fps, 25 fps
Range of IR illumination	...	20 m
IR illuminator power adjustment	...	Automatic
Lens	2.0 mm F1.2	2.8 mm
View angle	140 °	<ul style="list-style-type: none"> • 89 ° (manufacturer data) • 83 ° (our tests result)
Video output	...	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch

OSD menu	...	✓
Vandal-proof	...	—
Main features	<ul style="list-style-type: none"> • ATLO-DBC5/CHIME wireless support • Possibility of expansion with an additional ATLO-DBC5/RELAY wireless relay • Micro SD memory cards up to 256GB support (possible local recording) • Various record modes - users can choose time range for recording during day and set the specific recording mode: recording from motion detection, manual recording, schedule recording, • Motion Detection, • PIR detector, • Indoor proximity cards and key-fobs reader, • ICR - Movable InfraRed filter • Day/night mode, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network • 5 on-line users, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging - Motion Detection, • Video recording - Motion Detection, Doorbell button, • Automatic events notification via Email messages • Lock control - Relay output • Tamper protections • Google Home, Amazon Echo compliance 	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Day/Night mode (color/b&w/auto) • Auto White Balance • Sharpness - sharper image outlines • Coaxial audio - HD-TVI only
Mount	Surface-mounted	...
Power consumption	...	≤ 2.8 W
Power supply	<ul style="list-style-type: none"> • 12 V DC / 1 A (power adapter included) • 48 V PoE (802.3af) 	12 V DC / 230 mA
Operation temp	...	-20 °C ... 60 °C

Housing	Aluminum + Plastic (ABS)	Dome - Metal
Color	Silver	Graphite
"Index of Protection"	IP44	IP67
Supported languages	...	Polish, English
Manufacturer / Brand	...	APTI
Operation temp	-20 °C ... 55 °C	...
Weight	<ul style="list-style-type: none"> • 0.22 kg - Wireless Video Doorbell • 0.046 kg - rain cover 	0.42 kg
Dimensions	<ul style="list-style-type: none"> • 141 x 87 x 25 mm - Wireless Video Doorbell • 147 x 94 x 40 mm - rain cover 	Ø 96 x 91 mm
Guarantee	2 years	2 years

