




	ACCESS CONTROLLER MC16-PAC-ST-1-KIT ROGER	ACCESS CONTROLLER ASC3202B DAHUA	ACCESS CONTROLLER WITH FACE RECOGNITION + READER ATLO-FR-601
			
	353.42 EUR 353.42 EUR	505.49 EUR 505.49 EUR	48.34 EUR 48.34 EUR
Number of served transitions	1 (two-way)	2	...
Support	...	Cooperation with the access control systems	...
Face recognition distance	0.5 m ... 1 m (max 1000 faces in the database)
Number of supported readers	4	• 2 pcs RS-485, • 2 pcs Wiegand	...
Number of users	unlimited (purchase of the appropriate license required)
RFID proximity reader built-in	Unique EM 125kHz - Number of supported proximity cards : 10 000
Number of media per ID	8 - Proximity card, PIN code, fingerprint, etc.
Fingerprint reader built-in	Memory of 600 fingerprint patterns
Buffer memory	8 000 000 events buffer
Range of IR illumination	5 m
Number of access zones	4
White light LED illuminator range	—
Video output	—
Number of alarm zones	4
Wiegand interface	✓
RS-485 interface	—
Battery backup support	12 V / 20 Ah	—	...
Alarm inputs / outputs	...	2 / 2	0 / 1 - Relay output
Communication	• Ethernet - RJ-45 socket • RACS 5 v2 (Roger) • RS-485 interface	• 3 x RS-485, • 2 x Wiegand 34/26, • 1 x Ethernet 10 / 100 Mbps (RJ-45)	...

Main features	<ul style="list-style-type: none"> • Built-in LCD display showing the image from the video camera • Identification modes : Face recognition, Fingerprint, Proximity identifier Unique EM 125kHz, Any combination of the above • Wiegand 26 • LEDs and buzzer • Buzzer for acoustic signaling of some system events
Network protocols	...	P2P, IPv4, DNS, DDNS, TCP, UDP, ONVIF CGI	...
Operation modes	...	<ul style="list-style-type: none"> • Main control mode • Sub control mode 	...
"Index of Protection"	IP65
Operation temp	-40 °C ... 60 °C



Main features	<ul style="list-style-type: none"> • Metal housing • Integrated support in VISO ST software • Functions in the VISO ST system: <ul style="list-style-type: none"> - MSSQL database - work in distributed systems - multi-station work - monitoring of transitions with video preview - T&A event reporting - maximum number of transitions in the system : 128 	<ul style="list-style-type: none"> • Support for 2 doors (2x door sensor, 2x exit button, 2x alarm line, 2x lock control) • 1000 indexed users • Support up to 3000 finger prints • Memory of 5000 RFID cards • Support storage of 300 000 records • 128 General Purpose Schedules • Identification modes : RFID card, remote access, PIN, Fingerprint - Any combination of the above • Tamper protections • Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress • Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value • Beep signal - Buzzer • White list, Black list • Web-Server built-in • Software update via network • Monitoring and configuration through network - SmartPSS Lite application • Power output 12 V DC / 1 A - supplying power to the lock • Support hardware I/O port configuration and export configuration diagrams • ONVIF compliance 	...
Power supply	<ul style="list-style-type: none"> • 17 ... 22 V AC • 10 ... 15 V DC • 22 ... 26 V DC 	<ul style="list-style-type: none"> • 12 V DC / 2.5 A • PoE (802.3at) 	12 V DC
Power consumption	...	<ul style="list-style-type: none"> • ≤ 2 W (standby) • max. 20.4 W @ 12 V (operation) • max. 14.4 W @ PoE (operation) 	<ul style="list-style-type: none"> ≤ 3.6 W (operation) ≤ 2.2 W (standby)



Housing	...	Plastic (PC + ABS)	Aluminum + Tempered glass, Vandal-proof
Color	...	White	Silver + Black
IK rating	...	IK06	...
Operation temp	5 °C ... 40 °C	-10 °C ... 55 °C	...
Permissible relative humidity	10 % ... 95 % (non-condensing)	5 % ... 95 % (non-condensing)	...
Weight	3.9 kg	0.72 kg	0.38 kg
Dimensions	405 x 365 x 120 mm	186 x 186 x 58 mm	170 x 70 x 24 mm
Manufacturer / Brand	ROGER	DAHUA	ATLO
Guarantee	3 years	3 years	2 years