



	AHD, HD-CVI, HD-TVI, PAL SPEED DOME CAMERA OUTDOOR SD42215-HC-LA - 1080p 5 ... 75 mm DAHUA	EXPANSION PLUG KS-10/6X60 KLIMAS
		
	7027.99 NOK 7027.99 NOK	1.98 NOK 1.98 NOK
Material	...	<ul style="list-style-type: none"> • Expansion plug, Polypropylene • Screw, Steel galvanized
Standard	AHD, HD-CVI, HD-TVI, PAL	...
Drilling diameter	...	10 mm
Expansion plug length	...	60 mm
Screw dimensions	...	Ø 6 x 60 mm, SW-10
Resolution	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	...
Sensor	1/2.8 " STARVIS™ CMOS	...
IR illuminator	—	...
Application	...	<ul style="list-style-type: none"> • Concrete • Solid clay brick • Solid sand-lime brick
Lens	5 ... 75 mm	...
View angle	59 ° ... 5 °	...
Optical zoom	x 15	...
Digital zoom	x 16	...
Rotation speed depending on ZOOM level	✓	...
Horizontal rotation range	360 ° continuous	...
Vertical rotation range	-2 ° ... 90 °	...
Rotation speed (manual control)	<ul style="list-style-type: none"> • 0.1 °/s ... 300 °/s (horizontal), • 0.1 °/s ... 200 °/s (vertical) 	...
Preset rotation speed	<ul style="list-style-type: none"> • 300 °/s (horizontal) • 200 °/s (vertical) 	...
PTZ control	Via interface RS-485	...
Protocols	Pelco-D, Pelco-P, DH-SD (auto detection)	...
Video output	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp 75 Ω	...
Audio	<ul style="list-style-type: none"> • External microphone input • Audio support via coaxial cable - HD-CVI only 	...
Number of presets	300	...

Route settings	8	...
Horizontal scan	✓	...
Park action	—	...
Alarm inputs / outputs	2 / 1	...
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • EIS - Electronic Image Stabilization • F-DNR (Defog) - Reduction of image noise caused by precipitation • D-ZOOM - Digital Zoom • Image rotation and mirror • ICR - Movable InfraRed filter • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • 24 Configurable Privacy Zones • AGC - Automatic Gain Control 	...
OSD menu	✓	...
Power supply	12 V DC (power adapter included)	...
Power consumption	<ul style="list-style-type: none"> • ≤ 9.6 W (typical) • ≤ 12 W (max) 	...
Housing	Speed Dome, Metal	...
Color	White	...
"Index of Protection"	IP66	...
Mechanical protection class	IK10	...
Operation temp	-30 °C ... 60 °C	...
Weight	1.8 kg	...
Dimensions	Ø 170 x 155 mm	...
Supported languages	Polish, English	...
Manufacturer / Brand	DAHUA	KLIMAS
Guarantee	3 years	2 years