



	<a href="#">POWER GENERATOR DY-10020A-PRO 10 kW SENCI Dynamo</a>	<a href="#">SWITCH POE RG- NBS3200-48GT4XS-P 48- PORT REYEE</a>
		
	2555.79 EUR 2555.79 EUR	1407.83 EUR 1407.83 EUR
Nominal power	10 kW , 3 kW - for a single-phase socket	...
Maximum power	11 kW	...
Output voltage	• 230 V AC, • 400 V AC	...
LAN ports	...	• 48 x RJ45 10/100/1000 Base-T ( 48 x PoE (802.3af/at) ), • 4 x port SFP+ - Uplink
Management	...	✓
Transmission speed	...	10/100/1000 Mbps - 48 x Gigabit Ethernet 10 Gb/s - 4 x port SFP+
Number of outlets	1 pcs - three-phase, 32 A IEC 60309 , 2 pcs - single-phase, 16 A CEE 7/4 (Schuko)	...
Output frequency	50 Hz	...
Maximal total power	...	370 W
Switching capacity	...	176 Gb/s
ATS compatible	✓	...
Forwarding rate	...	130.95 Mpps
Built-in voltmeter	✓	...
MAC addresses table	...	16k
Voltage stabilization	AVR	...
Frequency measurement in Hz	✓	...
Certificates	...	CE, RoHS
Measuring the number of engine hours	✓	...
Number of fan coolers	...	1
12V DC output	✓	...
Mobile phones support	...	Android: Free application <a href="#">Ruijie Reye</a> iOS (iPhone): Free application <a href="#">Ruijie Reye</a>
Engine power	18 HP	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Jumbo Frame	...	9 kB
Engine capacity	688 cm <sup>3</sup>	...
Default IP address	...	10.44.77.200
Engine type	SV690 - V-shaped, 2-cylinder, gasoline, air cooled	...
Starting the engine	Electric - starter motor	...
Noise level during operation	90 dB	...
Average fuel consumption	5.6 l/h	...
Fuel tank capacity	45 l	...
Fuel gauge	✓	...
Operation temp	...	0 °C ... 50 °C
Main features	<ul style="list-style-type: none"> <li>• Low oil level indicator light</li> <li>• Overload protection</li> <li>• Display of operating parameters : voltage, frequency, engine hours since the engine was last started, total engine hours</li> <li>• High mobility of the device thanks to the attached wheels</li> <li>• 12V / 36Ah battery - included</li> </ul>	<ul style="list-style-type: none"> <li>• Can be mounted in a Rack cabinet</li> <li>• Switch is managed through the web and the cloud (Ruijie Reeye application)</li> <li>• Access Control List - ACL package filtering based on source and destination IP addresses</li> <li>• IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs</li> <li>• DHCP client</li> <li>• BPDU Filtering/Guard</li> <li>• Loop back detection</li> <li>• Spanning Tree STP/RSTP</li> <li>• Errdisable Recovery</li> <li>• Up to 16 aggregation groups and up to 8 ports per group</li> <li>• IGMP Snooping V1/V2/V3</li> <li>• DHCP snooping support</li> <li>• Port mirroring function</li> <li>• Loop Protection</li> <li>• IEEE802.3x Flow Control</li> <li>• MTBF (Mean Time Between Faults) &gt; 200.000 h</li> </ul>
Permissible relative humidity	...	10 % ... 90 % (non-condensing)
Color	Black + Red	...
Protections	...	Protection against lightning discharges : 6 kV

Power supply	...	100 V ... 240 AC
Power consumption	...	≤ 448 W
Weight	170 kg	5.6 kg
Dimensions	730 x 600 x 780 mm	440 x 357 x 43 mm
Manufacturer / Brand	SENCI / Dynamo	RUIJIE / REYEE
Guarantee	2 years	5 years