







	MODULAR PLUG RJ45/6*P10	AHD, PAL, TP MOBILE DVR PROTECT-218 4 CHANNELS	ISOPROPYL ALCOHOL KONTAKT-IPA-PLUS/100 BOTTLE 100 ml AG TERMOPASTY	MULTI-PURPOSE AGENT K2-07/250ML SPRAY 250 ml K2	VIDEO SPLITTER RV-16/32- UHD/R19	ADAPTER AD-UTP-2W/WG 2 x RJ45
						
	0.97 GBP 0.97 GBP	381.83 GBP 381.83 GBP	1.24 GBP 1.24 GBP	2.73 GBP 2.73 GBP	132.08 GBP 132.08 GBP	4.40 GBP 4.40 GBP
Package	Bottle 100 ml	Spray 250 ml
Video inputs	...	4 pcs BNC
In package	10 pcs The price for package
Connectors type	• 1 Adapter : 2 x RJ-45 plug + 1 x RJ-45 socket • 2 Adapter : 1 x RJ-45 plug + 2 x RJ-45 socket
Length of the cable	3 cm
Video outputs	...	1 pcs VGA 1 pcs CINCH 1 pcs M12, 4-pin socket
Standard	...	AHD, CVBS, TCP/IP	• AHD / HD-CVI / HD-TVI - 8 Mpx 4K UHD, • CVBS - PAL, NTSC	...
Audio inputs	...	4 pcs CINCH
Connector type	RJ45 (8P8C) Plug 8 pin
Number of inputs	16 pcs BNC	...
Audio outputs	...	1 pcs CINCH
Attachment of connector elements	Crimping
Number of outputs	32 pcs BNC	...
Wire mounting	Clamping on each wire with 2-pin edge
Application	Twisted-pair cable
Bandwidth	0 ... 120 MHz (-3dB)	...
Material	PET
Inputs impedance	75 Ω	...
Example of application	• UTP cat. 6
Outputs impedance	75 Ω	...
Resolution of recording video files	...	1920 x 1080, 1280 x 720, 960 x 576, 720 x 576, 704 x 576 px
Application	Ideal for removing dirt from optical components	• Elimination of squeaks, • Lubrication, • Removal of water, • Penetration, • Corrosion protection, • Surface preservation, • Removal of dirt
Input protection	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t _r =8/20µs)	...
Outputs protection	ESD, IEC 61000-4-2, ±30kV contact, ±30kV air Lightning, IEC 61000-4-5, 12A (t _r =8/20µs)	...
Main features	• Very easy and quick assembly • To crimp use the crimping tool HT-546	• Spray formulation with a straw for easy application in hard-to-reach places • Dual applicator - broad stream for application on a larger surface and precise stream (with a straw) for hard-to-reach places • It can be used in any position, even upside down
Current consumption	120 mA @ 12 V DC	...
Gain	0 dB	...
Housing type	1 U Rack 19"	...
Maximal total frame rate	...	• 100 fps @ 4 x AHD 1080p, • 100 fps @ 4 x CVBS 960H, • 25 fps @ 1 x IP 1080p
Supported hard drives	...	1 x 2 TB HDD / SSD 2.5 "

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Manufacturer / Brand	AG TERMOPASTY	K2	DELTA	...
Memory storage for video recording	...	0.4 GB/h @ 1920 x 1080 px H.265 15 fps
Image compression method	...	H.265 / H.264
GPS	...	✓
G-Sensor	...	3-axis
Gyroscope	...	3-axis
RS-485	...	✓
RS-232	...	✓
Alarm inputs / outputs	...	8 / 1
microSD socket	...	✓
Port USB	...	1 x USB 3.0
Ethernet port	...	1 x RJ-45 Passive PoE
Wi-Fi Module	...	2.4 GHz, 5 GHz - IEEE 802.11 a/b/g/n/ac
Main features	...	<ul style="list-style-type: none"> • Powering the cameras with 12V DC/3A voltage directly from recorder : 4 x DC 2.1/5.5mm socket + 1 x Passive PoE • Auto recording after power on • Power supply backup - Continuing to record after a short power failure (up to 8 s) • Cooperation with DSM cameras testing the driver's behavior • Cooperation with ADAS cameras testing the movement of the vehicle • Alarms and maintenance events registration • Alarms and errors memory reading Recording of the traveled route of the vehicle using the GPS receiver • The GPS, G-Sensor and gyroscope sensors enable detection of such events as: collision, sharp braking, accelerating or cornering too fast • Integration with vehicle sensors • Backup to USB drive (pendrive, external drive) • Backup to micro SD memory card • Wi-Fi support - Automatic data synchronization • Default administrator password : 888888 • Remote control • Compliance with the MIL-STD-810G standard • Automatic heating of the HDD/SSD slot allows you to start recording at temperatures from -40°C • Mirror - Mirror image
Power supply	...	8 V ... 36 V DC	7 ... 26 V DC (power adapter not included)	...
Power consumption	...	< 0.5 W (Standby mode) < 36 W (operation)
Operation temp	...	-40 °C ... 80 °C
Permissible relative humidity	...	20 % ... 95 % RH
Weight	0.002 kg	1.72 kg	0.1 kg	0.23 kg	0.44 kg	0.044 kg (total)
Dimensions	...	• 195 x 184 x 61 mm • 248 x 184 x 61 mm + additional cable housing	Ø 38 x 165 mm	Ø 52 x 199 mm	490 x 44 x 38 mm	• 1 Adapter : 115 x 19 x 19 mm • 2 Adapter : 120 x 30
Supported languages	...	English
Guarantee	2 years	2 years	5 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00