






	<a href="#">RFID PROXIMITY CARD ATLO-114*P100</a>	<a href="#">13.56 MHZ S50 PROXIMITY CARD IC-S50 DAHUA</a>	<a href="#">RFID PROXIMITY CARD ATLO-104N*P50</a>	<a href="#">END CLAMP PV-KK/35-50/B FOR SOLAR PANELS 35 mm</a>	<a href="#">FLUSH BOX S-60GW SIMET</a>
					
	38.16 GBP 38.16 GBP	1.63 GBP 1.63 GBP	14.29 GBP 14.29 GBP	0.53 GBP 0.53 GBP	0.66 GBP 0.66 GBP
Number of sections	...	...	...	...	1
Height	...	...	...	35 mm	...
"Index of Protection"	...	...	...	...	IP20
Hole diameter	...	...	...	9 mm	...
In package	<b>100 pcs The price for package</b>	...	<b>50 pcs The price for package</b>	...	...
mounting screw	...	...	...	—	...
Standard	Unique EM 125kHz	13.56 MHz S50	Unique EM 125kHz	...	...
Compatibility	EM4100/4102	ISO/IEC 14443A	EM4100/4102	...	...
Possibility of programming the serial number (ID)	—	—	—	...	...
Ability to write to internal memory	—	✓	—	...	...
Serial Number overprint	—	—	✓	...	...
Material	...	...	...	Aluminum	halogen free and inflammable
Color	...	...	...	Black	Blue
Main features	<ul style="list-style-type: none"> <li>• Range : ~ 15 cm</li> <li>• The TK-4100 chip</li> </ul>	Range : ~ 10 cm	<ul style="list-style-type: none"> <li>• Serial Number Format : 8H10D + WEG24A</li> <li>• Range : ~ 11 cm</li> <li>• The TK-4100 chip</li> </ul>	...	<ul style="list-style-type: none"> <li>• Flush-mounted, serial, deep</li> <li>• Class V0</li> <li>• 850 °C flammability index</li> <li>• 4 fixing points</li> <li>• 2 Mounting screws - included</li> </ul>
Weight	0.006 kg	0.006 kg	0.006 kg	0.22 kg	0.024 kg
Mounting holes distance	...	...	...	...	60 mm
Dimensions	85 x 54 x 2 mm	86 x 54 x 0.8 mm	86 x 54 x 1 mm	50 x 38 x 28 mm	84 x 67 x 80 mm
Manufacturer / Brand	ATLO	DAHUA	ATLO	...	SIMET
Guarantee	2 years	3 years	2 years	2 years	2 years