



	SWITCH POE APTI-POE0802G-120W-V2 8-PORT	IP SPEED DOME CAMERA OUTDOOR IPC6312LR-AX4W-VG Wi-Fi, - 1080p 2.8 ... 12 mm UNIVIEW
		
	63.75 EUR 63.75 EUR	372.17 EUR 372.17 EUR
Standard	...	TCP/IP
LAN ports	10 x RJ45 (8 x PoE (802.3af/at))	...
Sensor	...	1/2.7 " Progressive Scan CMOS
Management	—	...
Matrix size	...	2.1 Mpx
LED diodes	LAN, PoE	...
Resolution	...	1920 x 1080 - 1080p 1280 x 720 - 720p
Lens	...	2.8 ... 12 mm
Transmission speed	<ul style="list-style-type: none"> • 10 / 100 / 1000 Mbps : 2 x Port LAN, • 10 / 100 Mbps : 8 x LAN & PoE ports 	...
Maximal output power	30 W / port PoE	...
Maximal total power	120 W	...
View angle	...	<ul style="list-style-type: none"> • 105 ° ... 29 ° (manufacturer data) • 83 ° ... 30 ° (our tests result)
MAC addresses table	2k	...
Optical zoom	...	x 4
Digital zoom	...	—
Range of IR illumination	...	50 m
Video output	...	—
Main features	<ul style="list-style-type: none"> • 2 x Port Uplink • Range PoE : 250 m - The EXTEND mode enabled • Mounts for mounting the device in the RACK 10" system 	...
Preset rotation speed	...	<ul style="list-style-type: none"> • 50 °/s (horizontal) • 40 °/s (vertical)
Certificates	CE	...
Operation temp	-10 °C ... 55 °C	...
Rotation speed (manual control)	...	<ul style="list-style-type: none"> • 0.1 °/s ... 50 °/s (horizontal), • 0.1 °/s ... 40 °/s (vertical)
Horizontal rotation range	...	0 ° ... 345 ° - Rotation of the head is limited by stops
Vertical rotation range	...	-10 ° ... 110 °

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

RS-485 interface	...	—
Number of presets	...	256
Horizontal scan	...	—
Route settings	...	16
Image compression method	...	Ultra H.265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	<ul style="list-style-type: none"> • Microphone built-in, • Speaker built-in • Bi-directional audio streaming support • Audio detection • Noise reduction
Main stream frame rate	...	25 fps @ 1080p
Network interface	...	<ul style="list-style-type: none"> • Wi-Fi, 2.4 GHz, IEEE 802.11 b/g/n, • 10/100 Base-TX (RJ-45)
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓
Memory card slot	...	Micro SD memory cards up to 256GB support (possible local recording)
Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EZView • iOS (iPhone): Free application EZView
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream

Main features	...	<ul style="list-style-type: none"> • Intelligent Object Tracking • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • F-DNR (Defog) - Reduction of image noise caused by precipitation • Support ARP defence • BLC/HLC - Back Light / High Light Compensation • Day/night mode • ICR - Movable InfraRed filter • Auto White Balance • RESET button - on the cable • Privacy zones - max. 4 • Motion Detection • Tamper signaling • Image rotation and mirror • ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its • NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network • Home Position - set the camera to the specified position if no operator activity for a specified dwell time • Intelligent image analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, abandoned/missing object, scene changing, people counting, crowd gathering estimation, face detection
Housing	...	Speed Dome, Plastic
Color	...	White + Black
"Index of Protection"	...	IP66
Vandal-proof	...	—
Power supply	230 V AC	12 V DC / 1 A
Power consumption	...	≤ 12 W
Operation temp	...	-20 °C ... 60 °C
Weight	0.84 kg	0.85 kg
Dimensions	200 x 118 x 44 mm	Ø 133 x 185 x 276 mm (without bracket)
Supported languages	...	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian
Manufacturer / Brand	APTI	UNIVIEW
Guarantee	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00