






	PROXIMITY READER WITH KEYPAD ASR1101A DAHUA	SPEAKER CABLE HI-FI/2X1.0	WIRELESS DOOR CHIME ATLO-DBB-TUYA	WIRELESS VIDEO DOORBELL ATLO-DBC1-TUYA Wi-Fi, Tuya Smart	COAXIAL CABLE TRI-LAN-240 50 Ω
					
	899.86 NOK 899.86 NOK	6.09 NOK 6.09 NOK	68.46 NOK 68.46 NOK	371.00 NOK 371.00 NOK	11.06 NOK 11.06 NOK
Signaling mode	Optical - sound signaling
Cards support	13.56 MHz S50
Number of ring-tones	52
Sensor	Progressive Scan CMOS - 2 Mpx	...
Reading distance of prox-keys	max. 8 cm
Autonomous operation	—
Keyboard built-in	✓
In section	...	100 m . Price for 1m when buying a whole roll	100 m . Price for 1m when buying a whole roll
Resolution	1920 x 1080 px - 1080p	...
Doorbell button	—
Volume adjustment	4 volume levels, 10 ... 90 dB
Lens	2.5 mm	...
Communication	RS-485
Operation range	80 m in open area
Tamper output	✓
Inner conductor	...	2 x Ø 1.0 mm Cu-OFC Stranded wire	Ø 1.4 mm Cu ± 0.02 mm Wire
Frequency band	433.92 MHz ± 0.2
View angle	• 135 ° (manufacturer data) • 101 ° (our tests result)	...
Dielectric	Ø 3.8 mm Physical foam
IR illuminator	10 m	...
Maximal current consumption	180 mA
Coating color	...	Colorless
LED illuminator	—	...
Power consumption	≤ 0.5 W
Shield	Foil - Al/PET/Al
Wireless transmission range	The range limited only by the availability of the Wi-Fi network	...
Wi-Fi standard	IEEE 802.11 b/g/n : 2.4 GHz	...
Operation temp	-30 °C ... 60 °C
Braid	112 x Ø 0.12 mm Stranded wire CuSn
Network interface	Wi-Fi : 2.4 GHz	...
Permissible relative humidity	10 ... 95 % (non-condensing)
Impedance	50 Ω
Mobile phones support	The Tuya Smart free application on Android The Tuya Smart free application on iOS	...
Outer coating	...	PVC	Ø 6.1 mm ± 0.02 mm PE
Image compression method	H.264 / MJPEG / JPEG	...
Manufacturer / Brand	DAHUA

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

Main features	<ul style="list-style-type: none"> • Blue backlight of the keys • Touch control keys 	...	<ul style="list-style-type: none"> • Low power consumption • Receiver sensitivity : -110 dBm • Simple and quick device installation 	...	<ul style="list-style-type: none"> • low attenuation • perfect matched • high screening efficiency • it can be used in WLAN 2,4GHz and 5GHz installations • Operation temp : -40 °C ... 70 °C • Minimal bend radius : 30 / 60 mm
Main features	<ul style="list-style-type: none"> • Micro SD memory cards up to 128GB support (possible local recording), • PIR detector - Motion Detection, Detector range 3 m, • loitering detection • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • BLC - Back Light Compensation, • Microphone built-in, • Speaker built-in, • Bidirectional communication, • Noise and echo reduction • Full support via network : WiFi, • Possibility to work in cloud - you don't need to redirect the ports, • Video PUSH personal messaging • Increased battery life • Low current consumption • Operating frequency - Wireless doorbell : 433 MHz 	...
Mount	Surface-mounted	...
Cable attenuation at 100m section	Temperature : 20 °C 4.2 dB @ 30 MHz 5.4 dB @ 50 MHz 9.2 dB @ 150 MHz 11.2 dB @ 220 MHz 16.2 dB @ 450 MHz 23.3 dB @ 900 MHz 30.7 dB @ 1500 MHz 33.9 dB @ 1800 MHz 35.9 dB @ 2000 MHz 40.6 dB @ 2500 MHz 65.2 dB @ 5800 MHz
Power supply	12 V DC ± 10%	...	100 ... 240 V AC	<ul style="list-style-type: none"> • 2 x 18650 battery 3.7 V / 2600 mAh (not included) • 5 V DC - Charging via micro USB port (cable included) 	...
Housing	Plastic	...	Plastic	Waterproof - Plastic	...
Color	Silver / Black	...	Black	White / Black	...
"Index of Protection"	IP55	IP66	...
Weight	0.18 kg	...	0.06 kg	<ul style="list-style-type: none"> • 0.084 kg - Wireless Video Doorbell • 0.028 kg - mounting base 	...

Maximum transmitted power	1.41 kW @ 30 MHz 1.09 kW @ 50 MHz 0.62 kW @ 150 MHz 0.51 kW @ 220 MHz 0.35 kW @ 450 MHz 0.24 kW @ 900 MHz 0.19 kW @ 1500 MHz 0.17 kW @ 1800 MHz 0.16 kW @ 2000 MHz 0.14 kW @ 2500 MHz 0.09 kW @ 5800 MHz
Dimensions	87 x 136 x 13 mm	...	82 x 82 x 65 mm	<ul style="list-style-type: none"> • 142 x 46 x 32 mm - Wireless Video Doorbell • 158 x 62 x 17 mm - mounting base 	...
Guarantee	3 years	2 years	2 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00