



	UPS AT-UPS650-LED 650 VA EAST	HUB USB 3.0 HUB- USB3.0-1/7 55 cm
		
	59.50 EUR 59.50 EUR	9.93 EUR 9.93 EUR
Nominal power	390 W	...
Apparent Power	650 VA	...
Input voltage	165 V ... 275 V AC	...
Connectors	...	<ul style="list-style-type: none"> • 1 x socket - USB 3.0 Micro B • 7 x socket - USB 3.0 A • 1 x Power socket - 1.35 / 3.50 mm
Input frequency	50 / 60 Hz (auto detection)	...
Length of the cable	...	55 cm
USB standard	...	3.0
Output voltage	230 V AC \pm 10 % (Approximated Sine Wave)	...
Output frequency	50 / 60 Hz \pm 1 %	...
Transfer time	\leq 10 ms	...
Charging time (recover to 90% capacity)	8 hours	...
Battery	1 pcs - 12V/7Ah	...
Estimated battery operation time	<ul style="list-style-type: none"> • 16 minutes @ 100 W • 7 minutes @ 200 W • 4 minutes @ 300 W 	...
Number of outputs	2 pcs CEE 7/3 (Schuko)	...
Protections	<ul style="list-style-type: none"> • Fuse • Overvoltage • Overload protection • Overcharge protection • Telephone line filter 	...
Operation state indication	<ul style="list-style-type: none"> • LED diodes, • Sound signaling 	...
Main features	<ul style="list-style-type: none"> • Auto restart while AC is recovering • Automatic Voltage Regulator (AVR) • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Configurable alarm 	<ul style="list-style-type: none"> • Solid workmanship • It can be used as a charger for multiple devices when connected to an external power source via the 3.50 / 1.35 mm socket • LED indication • The cable included in the kit: USB 3.0 A plug / USB 3.0 Micro B plug • Each socket has a separate switch

Application	<ul style="list-style-type: none"> • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment 	...
Housing type	Tower	...
Operation temp. / Relative humidity	0 °C ... 40 °C / 20 ... 90 %	...
Weight	5.36 kg	0.050 kg
Dimensions	330 x 163 x 95 mm	165 x 36 x 25 mm
Manufacturer / Brand	EAST	...
Guarantee	2 years	2 years