





	RESIDUAL CURRENT CIRCUIT BREAKER LE-411510 ONE-PHASE, AC TYPE 30 mA 40 A LEGRAND	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA15FR3-G(H2) - 5 Mpx 3.6 mm	CABLE PROTECTOR ATLO-KP-16X400	INSULATION STRIPPER HT-332
				
	33.37 CHF 33.37 CHF	33.55 CHF 33.55 CHF	5.92 CHF 5.92 CHF	2.96 CHF 2.96 CHF
Material	Stainless steel	PET
Device type	Residual current circuit breaker, One-phase, AC type
Standard	...	AHD / HD-CVI / HD-TVI / PAL
Rated sensitivity	30 mA
Rated current	40 A
Application	Coaxial cable RG58 RG59 RG6
Number of poles	2
Breaking capacity	10000 A
Rated voltage	230 V AC / 50 Hz
Connectors type	screw terminals
Resolution	...	2704 x 1950 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p
Sensor	...	1/2.5 " Progressive Scan CMOS
Main features	<ul style="list-style-type: none"> • Can be equipped with DX3 series signalling and remote tripping auxiliaries and motorised controls • Provided space for a label with description • Can be connected with using the supply busbars fork-type or prong-type 	...	Metal ends	Left shield width adjustment
Lens	...	3.6 mm, F1.2
View angle	...	• 100 °
Range of IR illumination	...	30 m
IR illuminator power adjustment	...	Automatic
Width in 17.5 mm modules	2
Video output	...	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
OSD menu	...	OSD menu available via BCS-XVR recorder

Main features	...	<ul style="list-style-type: none"> • D-WDR - Wide Dynamic Range • BLC - Back Light Compensation • 3D-DNR - Digital Noise Reduction • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance
Power supply	...	12 V DC / 420 mA
Power consumption	...	< 5 W
Housing	Plastic, DIN, TS-35 rail mounting	Dome, Metal
Color	...	Graphite	Silver	...
"Index of Protection"	...	IP66
Mechanical protection class	...	—
Operation temp	...	-20 °C ... 60 °C
Weight	0.186 kg	0.3 kg	0.21 kg	...
Dimensions	36 x 83 x 75 mm	Ø 80 x 94 mm	<ul style="list-style-type: none"> • Ø 16 mm - Inner diameter, • Ø 20 mm - External diameter, • 400 mm - Length (CABLE PROTECTOR) • 480 mm - Total length 	...
Manufacturer / Brand	LEGRAND	BCS
Guarantee	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00