




|   | <a href="#">ACCESS POINT +ROUTER<br/>TL-MERC-MW300D 300Mb/s<br/>ADSL TP-LINK / MERCUSYS</a> | <a href="#">POWER DISTRIBUTION<br/>UNIT AK-SP-05A AKYGA</a>                        | <a href="#">WIRELESS PIR DETECTOR<br/>PMD-75 PARADOX</a>                            |
|---|---|--|---|
|   |            |  |  |
|   | 9299.04 HUF<br>9299.04 HUF  | 3634.62 HUF<br>3634.62 HUF   | 27403.85 HUF<br>27403.85 HUF  |
| Support                                     | ...   | ...  | PARADOX MAGELLAN  |
| Rated voltage                               | ...   | 230 V AC / 50 Hz   | ...   |
| Total maximal current                       | ...   | 10 A   | ...   |
| Antenna type                                | 2 x Omnidirectional antenna   | ...  | ...   |
| Battery power supply                        | ...   | ...  | 3 x AAA - Alkaline batteries  |
| Maximal total load                          | ...   | 2500 W   | ...   |
| Standards                                   | IEEE 802.11 b/g/n   | ...  | ...   |
| Battery lifetime                            | ...   | ...  | ~ 3 years   |
| Frequency range                             | 2.4 ... 2.4835 GHz  | ...  | 433 MHz   |
| Response time                               | ...   | < 25 ns  | ...   |
| Radio communication range<br>(at open area) | ...   | ...  | max. 75 m   |
| Number of outlets                           | ...   | 5 grounded outlets<br>10A/250V   | ...   |
| Recommended installation<br>height          | ...   | ...  | 2.1 ... 2.7 m above floor<br>level  |
| Automatic delayed fuse                      | ...   | 10 A / 250 V   | ...   |
| LAN ports                                   | 3x RJ-45 ( 10/100 Mbps,<br>Auto MDI/MDX )   | ...  | ...   |
| Detection angle / Detection<br>range        | ...   | ...  | 90 ° / 11 m (basic lens)  |
| Nominal voltage of surge<br>suppressor      | ...   | 250 V / 50 Hz  | ...   |
| WAN interface                               | 1x RJ-11<br>ADSL/ADSL2/ADSL2+<br>Annex A  | ...  | ...   |
| Baud rates                                  | 300 Mbps  | ...  | ...   |
| Pet immunity                                | ...   | ...  | max. 40 kg  |
| Environment class                           | ...   | ...  | Grade 2   |
| DC filter to eliminate<br>interferences     | ...   | RFI ≤ 10 dB  | ...   |
| Maximum stroke current                      | ...   | 4.5 kA   | ...   |
| Maximum energy absorption                   | ...   | 150 J  | ...   |
| Switch                                      | ...   | with light indication  | ...   |

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10  
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl  
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

|                               |   |                  |  |
|-------------------------------|---|------------------|--|
| Length of the cable           | ...   | 1.8 m            | ...  |
| Housing                       | ...   | Plastic (ABS)    | ...  |
| Color                         | ...   | Black            | ...  |
| Receiver sensitivity          | 270M : -73dBm@10% PER<br>130M : -75dBm@10% PER<br>54M : -77dBm@10% PER<br>11M : -90dBm@10% PER<br>6M : -94dBm@10% PER<br>1M : -96dBm@10% PER  | ...              | ...  |
| DDNS                          | —   | ...              | ...  |
| DHCP server                   | ✓   | ...              | ...  |
| Compliance with standards     | ...   | ...              | EN 50130-4 EN 61000-6-3<br>EN 60950  |
| Port USB                      | —   | ...              | ...  |
| Country of origin             | ...   | ...              | Canada   |
| Firmware update               | ✓   | ...              | ...  |
| Transmitter power             | < 20 dBm  | ...              | ...  |
| Operation modes               | Access Point  | ...              | ...  |
| Protections                   | WPA-PSK/WPA2-PSK  | ...              | ...  |
| Management interface          | Web browser   | ...              | ...  |
| LED indicators                | Power ADSL, INTERNET,<br>WiFi LAN   | ...              | ...  |
| Main features                 | <ul style="list-style-type: none"> <li>• WPS/RESET button</li> <li>• Built-in 3-port switch</li> <li>• Guest Network - a separate and secure network for guests</li> <li>• Port forwarding</li> <li>• DMZ</li> <li>• DHCP client list</li> <li>• IPv4/IPv6</li> </ul> | ...              | <ul style="list-style-type: none"> <li>• 2 PIR detectors - Dual optics (two dual opposed element sensors)</li> <li>• Advanced temperature compensation</li> <li>• Patented detection analyzing (without signal analog processing)</li> </ul> |
| Operation temp                | 0 °C ... 40 °C  | 5 °C ... 50 °C   | 0 °C ... 50 °C   |
| Permissible relative humidity | 10 % ... 90 %   | ...              | ...  |
| Power supply                  | 9 V DC / 0.6 A (power adapter included)   | ...              | ...  |
| Weight                        | 0.12 kg   | 0.306 kg         | 0.156 kg   |
| Dimensions                    | 136 x 94 x 25 mm The DSL line splitter included   | 305 x 50 x 40 mm | 75 x 127 x 60 mm   |
| Manufacturer / Brand          | TP-LINK / MERCUSYS  | AKYGA            | PARADOX  |
| Guarantee                     | 2 years   | 2 years          | 2 years  |