

	WI-FI SMART PLUG ATLO-P2F-TUYA Wi-Fi, Tuya Smart	NVR TC-R324160 SPEC:E/B/N/V4.0 160 CHANNELS TIANDY
		
	10.31 EUR 10.31 EUR	10627.40 EUR 10627.40 EUR
Standard	...	TCP/IP
Rated voltage	220 ... 240 V AC	...
Supported resolutions	...	max. 16 Mpx
Maximal total load	3680 W	...
Total maximal current	16 A	...
Number of outlets	2 pcs	...
Socket type	CEE 7/3	...
Video outputs	...	2 pcs HDMI 4K 2 pcs VGA • Video outputs are independent of each other • Simultaneous video display for VGA1/HDMI1
Plug type	CEE 7/5	...
Audio support	...	Audio from cameras
Grounding	✓	...
Audio inputs	...	1 pcs
Audio outputs	...	1 pcs
Wireless	• Wi-Fi, 2.4 GHz - IEEE 802.11 b/g/n, • Bluetooth	...
Image compression method	...	S+265 / H.265 / S+264 / H.264
Supported hard drives	...	24 x 18 TB SATA + 1 x eSATA
Recording modes	...	Manual, Motion Detection, Schedule
External storage devices backup	...	Backup to USB drive (pendrive, external drive)
Searching and playback the records	...	• Records searching: by time and events type. Records playback: forward, backward, fast, slow • Advanced searching (to the one second accuracy) • Playback max. 16 cameras in the same time

Main features	<ul style="list-style-type: none"> • schedule, • timer, • remote access, • voice control • Energy measurement • ON/OFF button • STATUS indicator 	...
Housing	Plastic	...
Color	White	...
Operation temp	-20 °C ... 50 °C	...
Permissible relative humidity	≤ 80 %	...
Network interface	...	4 x RJ-45 - 10 / 100 / 1000 Mbps
Network functions	...	Full support via network, Remote records copying, Web-Server built-in
ONVIF	...	✓
Mobile phones support	<ul style="list-style-type: none"> • The Tuya Smart free application on Android • The Tuya Smart free application on iOS 	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Default IP address	...	DHCP or 192.168.1.2
Default admin user / password	...	admin / - The administrator password should be set at the first start
Web browser access ports	...	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports	...	3000, 3001
PC client access ports	...	3000, 3001
Port ONVIF	...	80
Alarm inputs / outputs	...	16 / 8
Motion Detection	...	✓
Intelligent image analysis	...	—
USB	...	2 x USB 2.0 + 1 x USB 3.0

RS232	...	1 pcs
RS485	...	2 pcs
Mouse support	...	✓
IR remote controller in the set	...	—
Main features	...	<ul style="list-style-type: none"> • Possibility of operation the disks in RAID JBOD/0/1/5/6/10/50/60 array Support for Intelligent Image Analysis function, available in TIANDY cameras : • crossing the line (tripwire) • double crossing the line • abandoned/missing object • detection of loitering in a given area • running • parking detection • heat map • scene changing • signal loss indication • License plate recognition • detection of persons on duty • detection of people gathering • Parking monitoring mode • protective helmet detection • people counting • advanced face capture features (max 100 000 faces in the database)
Power supply	...	100 V ... 240 V AC
Weight	0.13 kg	15.2 kg
Dimensions	97 x 50 x 83 mm	485 x 618 x 174 mm
Supported languages	...	Polish, English, Albanian, Arabic, French, Hebrew, Spanish, Dutch, Korean, German, Portuguese, Russian, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand	ATLO	TIANDY
Guarantee	2 years	3 years