

	POWER DISTRIBUTION UNIT ACAR-P2 (5 + 2 OUTLETS)	CLEANING PASTE PEVALIN PROFESSIONAL/250 TUBE 250 ml TESA	PLUG-IN MODULE FOR OVERVOLTAGE LIMITER LE-412297 2 TYPE 20 kA LEGRAND	IP CAMERA IPC-HFW2549S-S-IL-0360B WizSense - 5 Mpx 3.6 mm DAHUA	CONNECTOR FOR LED STRIPS AD-TL-6499Z/T/RGBW 12 mm ORNQ	ANGULAR PLUG LE-50103 230 V 16 A LEGRAND
	67.25 PLN 67.25 PLN	33.80 PLN 33.80 PLN	96.42 PLN 96.42 PLN	1140.00 PLN 1140.00 PLN	5.29 PLN 5.29 PLN	15.41 PLN 15.41 PLN
Standard	TCP/IP
Sensor	1/2.7" Progressive Scan CMOS
Rated voltage	230 V AC / 50 Hz	...	230 / 400 V AC, 50 / 60 Hz	230 V / 50 Hz
Application	Works with LED lighting RGBW	...
Package	...	Tube 250 ml
Maximal current load	16 A
Matrix size	5 Mpx
Total maximal current	10 A
Strip width	12 mm	...
Maximal voltage	320 V AC, 50 / 60 Hz
Grounding	✓
Maximal total load	2300 W
Electrical cable	max. 3 x 2.5 mm ²
Response time	< 25 ns
Cable terminals	screw terminals
Class	2 type (Class C)
Plug type	CEE 7/6
Maximal power voltage	48 V	...
Number of outlets	5 grounded outlets 10A/250V 2 non-grounded outlets 2.5A/250V
Protection level Up	1.2 kV @ 8/20 μs (T2)
Automatic delayed fuse	10 A / 250 V
Leak current	< 0.5 mA
Nominal discharge current	5 kA @ 8/20 μs (T2)
Nominal voltage of surge suppressor	250 V / 50 Hz
Protection level of surge suppressor	≤ 1.3 kV (L/N)
Operation state indication	✓
Main features	Varistor
Nominal stroke current	2 kA (L/N) - (8/20μs)
Switch	two-way, with light indication
Maximum stroke current	6.5 kA (L/N) - (8/20μs)	...	20 kA @ 8/20 μs (T2)
Length of the cable	1.45 m
Resolution	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.6 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Scanning system	Progressive
Lens	3.6 mm
View angle	• 92 ° (manufacturer data) • 88 ° (our tests result)
Range of IR illumination	30 m
White light LED illuminator range	30 m
Min. illumination	0.007 Lux / F1.0 (color)
RS-485 interface	-
Memory card slot	Micro SD memory cards up to 256GB support (possible local recording)
Image compression method	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs	-
Audio	• Microphone built-in • Audio transmission via network • Audio detection • Compliance with the AAC standard
Main stream frame rate	20 fps @ 5 Mpx 25 fps @ 4 Mpx
Network interface	10/100 Base-T (RJ-45)
Network protocols	IPv4/IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour
WEB Server	Built-in
Max. number of on-line users	20
ONVIF	21.12
Mobile phones support	Port no.: 37777 or access by a cloud (P2P) • Android: Free application DMSS • iOS (iPhone): Free application DMSS
Default IP address	192.168.1.108
Default admin user / password	admin / - The administrator password should be set at the first start
Web browser access ports	80, 37777

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00

PC client access ports	37777
Mobile client access ports	37777
Port ONVIF	80
RTSP URL	rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin.haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Main features	<ul style="list-style-type: none"> • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ROI - improve the quality of selected parts of image • BLC/HLC - Back Light / High Light Compensation • Possibility to change the resolution, quality and bit rate • Motion Detection • Configurable Privacy Zones • Mirror - Mirror image • SMD PLUS - searching for an object classified as: human, motor vehicle • IVS analysis : intrusion, crossing the line (tripwire) - classification of people and vehicles video tampering
Power supply	<ul style="list-style-type: none"> • PoE (802.3af) • 12 V DC / 380 mA
Power consumption	<ul style="list-style-type: none"> • ≤ 4.6 W @ 12 V DC • ≤ 5.5 W @ PoE
Housing	Plastic - non-flammable	...	Plastic	Compact - Metal
Color	White + Black	White	White
"Index of Protection"	IP67	---	...
Vandal-proof	---
Operation temp	-40 °C ... 60 °C
Weight	0.44 kg	...	0.042 kg	0.47 kg	0.002 kg	0.032 kg
Dimensions	370 x 65 x 44 mm	...	62 x 54 x 17 mm	166 x 70 x 70 mm	28 x 20 mm	84 x 37 x 44 mm
Supported languages	Polish, English, Czech, French, Spanish, Dutch, German, Russian, Portuguese, Romanian, Turkish, Ukrainian, Hungarian, Italian
Manufacturer / Brand	...	TESA	LEGRAND	DAHUA	ORNO	LEGRAND
Guarantee	2 years	2 years	2 years	3 years	2 years	2 years



DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
 Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
 Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00