



	<a href="#">HDD ENCLOSURE 25PW1-U3-BK-EP ORICO</a>	<a href="#">IP CAMERA IPC3614LE-ADF28KC-WL ColorHunter - 4 Mpx 2.8 mm UNIVIEW</a>
		
	7.48 EUR 7.48 EUR	165.87 EUR 165.87 EUR
Standard	...	TCP/IP
Sensor	...	1/3 " Progressive Scan CMOS
Matrix size	...	4 Mpx
Supported hard drives	1 x SATA III, 2.5 " - 6 TB (max)	...
Outputs	1 x USB 3.0 Micro B, max. 5 Gb/s	...
Operation state indication	LED diodes	...
Resolution	...	2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p
Lens	...	2.8 mm @ F1.6
View angle	...	• 113 ° (manufacturer data) • 97 ° (our tests result)
White light LED illuminator range	...	30 m
Range of IR illumination	...	30 m
S/N ratio	...	> 52 dB
RS-485 interface	...	—
Memory card slot	...	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method	...	Ultra 265 / H.265 / H.264 / MJPEG
Alarm inputs / outputs	...	—
Audio	...	• Microphone built-in, • Speaker built-in • Bi-directional audio streaming support • Audio transmission via network • Audio detection
Main stream frame rate	...	25 fps @ 4 Mpx
Network interface	...	10/100 Base-TX (RJ-45)
Network protocols	...	IPv4/IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL / TLS, IEEE 802.1x, SNMP
WEB Server	...	Built-in
Max. number of on-line users	...	32
ONVIF	...	✓

Mobile phones support	...	Access by a cloud (P2P) <ul style="list-style-type: none"> <li>• Android: Free application <a href="#">EZView</a></li> <li>• iOS (iPhone): Free application <a href="#">EZView</a></li> </ul>
Default IP address	...	DHCP or 192.168.1.13
Default admin user / password	...	admin / 123456
Web browser access ports	...	80, 554
PC client access ports	...	Port no.: 80 or access by a cloud (P2P) - PC: Free application <a href="#">EZStation</a>
Mobile client access ports	...	80
Port ONVIF	...	80
RTSP URL	...	rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream
Main features	...	<ul style="list-style-type: none"> <li>• ColorHunter - colorful night mode</li> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 2D-DNR, 3D-DNR - Digital Noise Reduction</li> <li>• F-DNR (Defog) - Reduction of image noise caused by precipitation</li> <li>• BLC/HLC - Back Light / High Light Compensation</li> <li>• WB - White Balance (ATW/AWB/manual/indoor/outdoor)</li> <li>• Day/Night mode (color/b&amp;w/auto)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its</li> <li>• NAS - Network Attached Storage support</li> <li>• Possibility to change the resolution, quality and bit rate</li> <li>• Sharpness - sharper image outlines</li> <li>• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms</li> <li>• Privacy zones - max. 4</li> <li>• Motion detection with human/vehicle silhouette recognition</li> <li>• Intelligent image analysis : crossing the line (tripwire), intrusion (human silhouette)</li> <li>• Overvoltage protection : 4 kV</li> </ul>

Power supply	5 V DC - from USB port	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 670 mA</li> </ul>
Power consumption	...	≤ 8 W
Housing	Plastic	Dome, Metal + Plastic
Color	...	White
"Index of Protection"	...	IP67
Vandal-proof	...	IK10
Operation temp	...	-30 °C ... 60 °C
Weight	0.06 kg	0.31 kg
Dimensions	130 x 80 x 14 mm	Ø 118 x 96 mm
Supported languages	...	Polish, English, Czech, Spanish, Dutch, French, German, Portuguese, Slovak, Hungarian, Italian
Manufacturer / Brand	ORICO	UNIVIEW
Guarantee	2 years	3 years